

## **Oracle® Application Server**

Adapter for IMS/TM User's Guide

10g Release 2 (10.1.2)

**B15805-01**

June 2005

Oracle Application Server Adapter for IMS/TM User's Guide, 10g Release 2 (10.1.2)

B15805-01

Copyright © 2003, 2005, Oracle. All rights reserved.

Primary Author: Amitai Sela

Contributors: Yishai Hadas, Dror Harari, Adeeb Massad, Meera Srinivasan, Bo Stern, Shashi Suravarapu, Costi Zaboura, Pratibha Singhal

The Programs (which include both the software and documentation) contain proprietary information; they are provided under a license agreement containing restrictions on use and disclosure and are also protected by copyright, patent, and other intellectual and industrial property laws. Reverse engineering, disassembly, or decompilation of the Programs, except to the extent required to obtain interoperability with other independently created software or as specified by law, is prohibited.

The information contained in this document is subject to change without notice. If you find any problems in the documentation, please report them to us in writing. This document is not warranted to be error-free. Except as may be expressly permitted in your license agreement for these Programs, no part of these Programs may be reproduced or transmitted in any form or by any means, electronic or mechanical, for any purpose.

If the Programs are delivered to the United States Government or anyone licensing or using the Programs on behalf of the United States Government, the following notice is applicable:

U.S. GOVERNMENT RIGHTS Programs, software, databases, and related documentation and technical data delivered to U.S. Government customers are "commercial computer software" or "commercial technical data" pursuant to the applicable Federal Acquisition Regulation and agency-specific supplemental regulations. As such, use, duplication, disclosure, modification, and adaptation of the Programs, including documentation and technical data, shall be subject to the licensing restrictions set forth in the applicable Oracle license agreement, and, to the extent applicable, the additional rights set forth in FAR 52.227-19, Commercial Computer Software—Restricted Rights (June 1987). Oracle Corporation, 500 Oracle Parkway, Redwood City, CA 94065

The Programs are not intended for use in any nuclear, aviation, mass transit, medical, or other inherently dangerous applications. It shall be the licensee's responsibility to take all appropriate fail-safe, backup, redundancy and other measures to ensure the safe use of such applications if the Programs are used for such purposes, and we disclaim liability for any damages caused by such use of the Programs.

Oracle, JD Edwards, PeopleSoft, and Retek are registered trademarks of Oracle Corporation and/or its affiliates. Other names may be trademarks of their respective owners.

The Programs may provide links to Web sites and access to content, products, and services from third parties. Oracle is not responsible for the availability of, or any content provided on, third-party Web sites. You bear all risks associated with the use of such content. If you choose to purchase any products or services from a third party, the relationship is directly between you and the third party. Oracle is not responsible for: (a) the quality of third-party products or services; or (b) fulfilling any of the terms of the agreement with the third party, including delivery of products or services and warranty obligations related to purchased products or services. Oracle is not responsible for any loss or damage of any sort that you may incur from dealing with any third party.

---

---

# Contents

<b>Preface</b> .....	vii
Audience .....	vii
Documentation Accessibility .....	vii
Related Documentation .....	viii
Conventions .....	viii
 <b>1 Introduction</b>	
<b>OracleAS Adapter for IMS/TM Overview</b> .....	1-1
<b>OracleAS Adapter for IMS/TM Architecture</b> .....	1-2
Integration Flow from Oracle Application Server to a Legacy Application .....	1-2
 <b>2 Installing and Configuring OracleAS Adapter for IMS/TM</b>	
<b>Preinstallation Tasks</b> .....	2-1
IBM OS/390 or z/OS Hardware and Software Requirements .....	2-1
Hardware Requirements .....	2-1
Software Requirements .....	2-2
Windows Hardware and Software Requirements .....	2-2
Hardware Requirements .....	2-2
Software Requirements .....	2-2
<b>Installing Oracle Connect on an IBM OS/390 or z/OS Series Platform</b> .....	2-3
Installation Worksheet .....	2-3
Preinstallation Instructions .....	2-4
Installing the Kit .....	2-5
Installation Instructions .....	2-5
Postinstallation Instructions .....	2-8
Postinstallation Procedures .....	2-8
Starting the Daemon .....	2-10
Setting Up Oracle Connect to Work Under IMS/TM .....	2-10
Setting Up Oracle Connect for Reentrancy .....	2-11
<b>Updating an Existing Oracle Connect Installation with IMS/TM</b> .....	2-12
<b>Installing Oracle Studio</b> .....	2-13
Installing Oracle Studio from the CD-ROM .....	2-14
<b>Configuring Oracle Connect</b> .....	2-14
Setting Up the IBM OS/390 or z/OS Platform in Oracle Studio .....	2-14
Securing Access to Oracle Connect .....	2-15

Setting Password Access to Oracle Studio .....	2-15
Specifying Users with Administrative Rights .....	2-16
Setting Up Run-time User Access to the IBM OS/390 or z/OS Platform .....	2-17
Modeling Interactions for OracleAS Adapter for IMS/TM.....	2-18
Setting Up an Oracle Connect Adapter .....	2-19
Generating Outbound Interactions .....	2-20
Generating Inbound Interactions .....	2-26
Viewing the XML Schema.....	2-32
Creating XML Schemas .....	2-32
<b>3 Integrating OracleAS Adapter for IMS/TM with OC4J</b>	
Integrating OracleAS Adapter for IMS/TM with OC4J.....	3-1
Configuring the J2CA 1.0 IMS/TM Adapter .....	3-2
Using the CCI API to Develop Applications .....	3-3
Configuring Multiple Adapters .....	3-4
Updating Configuration Information .....	3-4
<b>4 Integrating OracleAS Adapter for IMS/TM with Oracle BPEL Process Manager</b>	
Integrating OracleAS Adapter for IMS/TM with Oracle BPEL Process Manager.....	4-1
Using OracleAS Adapter for IMS/TM as Outbound Link.....	4-2
Using OracleAS Adapter for IMS/TM as Inbound Link.....	4-3
Updating Outbound and Inbound Interactions.....	4-4
<b>5 Troubleshooting OracleAS Adapter for IMS/TM</b>	
Troubleshooting the Daemon .....	5-1
Starting the Daemon .....	5-1
Task: Starting the Daemon .....	5-2
Shutting Down the Daemon.....	5-2
Monitoring the Daemon During Run Time.....	5-2
Daemon (Computer) Options .....	5-2
Workspace Options .....	5-3
Server Options.....	5-4
Daemon Logs .....	5-4
The Daemon Log Monitor .....	5-5
The Workspace Log Monitor.....	5-5
The Server Log Monitor .....	5-6
Resolving Communication Errors.....	5-6
Resolving Specific Errors.....	5-7
<b>6 Advanced Features of OracleAS Adapter for IMS/TM</b>	
Configuring the Daemon for High Availability .....	6-1
Adding a New Daemon Workspace Configuration.....	6-1
Editing the Workspace .....	6-2
Configuring the Server Mode.....	6-2
Configuring a Binding Environment .....	6-4
comm Category .....	6-5

debug Category .....	6-6
miscellaneous Category .....	6-6
odbc Category .....	6-8
oledb Category .....	6-8
optimizer Category .....	6-8
queryProcessor Category .....	6-8
transactions Category .....	6-9
tuning Category .....	6-9
<b>Migration Considerations</b> .....	6-9
<b>Security Considerations</b> .....	6-10
Setting Design Time Security .....	6-10
Setting Run-time Security .....	6-10
<b>Transaction Support</b> .....	6-11
 <b>A Advanced Tuning of the Metadata</b>	
<b>Metadata for the Back-end Adapter</b> .....	A-1
General Tab .....	A-1
Interaction Tab .....	A-2
Schema General Tab .....	A-3
Schema Record Tab .....	A-5
Source Tab .....	A-6
 <b>B IMS/TM Back-end Adapter Data Type Support</b>	
Data Type Mapping .....	B-1
 <b>C Advanced Tuning of the Daemon</b>	
Daemon Control .....	C-1
Daemon Logging .....	C-3
Daemon Security .....	C-5
Workspaces .....	C-7
WS Info. ....	C-8
WS Server .....	C-10
WS Logging .....	C-14
WS Security .....	C-16
 <b>D Globalization Settings</b>	
Defining the Language and Codepage .....	D-1

## Index



---

---

# Preface

This guide is the primary source of user and reference information on OracleAS Adapter for IMS/TM, which enables client applications to access transactions running under IMS/TM through the Sun J2EE Connector Architecture (J2CA) API.

This document describes the features of OracleAS Adapter for IMS/TM software that apply to the IBM OS/390, z/OS Series, Windows 2000, Windows XP, and Windows Server 2003 operating systems.

This preface covers the following topics:

- [Audience](#)
- [Related Documentation](#)
- [Conventions](#)

## Audience

This manual is intended for Oracle integration administrators who perform the following tasks:

- Installing and configuring OracleAS Adapter for IMS/TM
- Diagnosing errors
- Using either OracleAS to access IMS/TM transactions

---

---

**Note:** You should understand the fundamentals of OracleAS, OC4J, the IBM OS/390, z/OS Series and Microsoft Windows operating system before using this guide to install or administer OracleAS Adapter for IMS/TM.

---

---

## Documentation Accessibility

Our goal is to make Oracle products, services, and supporting documentation accessible, with good usability, to the disabled community. To that end, our documentation includes features that make information available to users of assistive technology. This documentation is available in HTML format, and contains markup to facilitate access by the disabled community. Accessibility standards will continue to evolve over time, and Oracle is actively engaged with other market-leading technology vendors to address technical obstacles so that our documentation can be accessible to all of our customers. For more information, visit the Oracle Accessibility Program Web site at

<http://www.oracle.com/accessibility/>

### Accessibility of Code Examples in Documentation

Screen readers may not always correctly read the code examples in this document. The conventions for writing code require that closing braces should appear on an otherwise empty line; however, some screen readers may not always read a line of text that consists solely of a bracket or brace.

### Accessibility of Links to External Web Sites in Documentation

This documentation may contain links to Web sites of other companies or organizations that Oracle does not own or control. Oracle neither evaluates nor makes any representations regarding the accessibility of these Web sites.

### TTY Access to Oracle Support Services

Oracle provides dedicated Text Telephone (TTY) access to Oracle Support Services within the United States of America 24 hours a day, seven days a week. For TTY support, call 800.446.2398.

## Related Documentation

Printed documentation is available for sale in the Oracle Store at

<http://oraclestore.oracle.com/>

To download free release notes, installation documentation, white papers, or other collateral, please visit the Oracle Technology Network (OTN). You must register online before using OTN; registration is free and can be done at

<http://www.oracle.com/technology/membership/>

If you already have a username and password for OTN, then you can go directly to the documentation section of the OTN Web site at

<http://www.oracle.com/technology/documentation/>

## Conventions

This section describes the conventions used in the text and code examples of this documentation set. It describes:

- [Conventions in Text](#)
- [Conventions in Code Examples](#)
- [Conventions for Windows Operating Systems](#)

### Conventions in Text

We use various conventions in text to help you more quickly identify special terms. The following table describes those conventions and provides examples of their use.

Convention	Meaning	Example
<b>Bold</b>	Bold typeface indicates terms that are defined in the text or terms that appear in a glossary, or both.	When you specify this clause, you create an <b>index-organized table</b> .



Convention	Meaning	Example
<i>Italics</i>	Italic typeface indicates book titles or emphasis.	<i>Oracle Database Concepts</i> Ensure that the recovery catalog and target database do <i>not</i> reside on the same disk.
UPPERCASE monospace (fixed-width) font	Uppercase monospace typeface indicates elements supplied by the system. Such elements include parameters, privileges, datatypes, RMAN keywords, SQL keywords, SQL*Plus or utility commands, packages and methods, as well as system-supplied column names, database objects and structures, usernames, and roles.	You can specify this clause only for a NUMBER column. You can back up the database by using the BACKUP command. Query the TABLE_NAME column in the USER_TABLES data dictionary view. Use the DBMS_STATS.GENERATE_STATS procedure.
lowercase monospace (fixed-width) font	Lowercase monospace typeface indicates executables, filenames, directory names, and sample user-supplied elements. Such elements include computer and database names, net service names, and connect identifiers, as well as user-supplied database objects and structures, column names, packages and classes, usernames and roles, program units, and parameter values.  <b>Note:</b> Some programmatic elements use a mixture of UPPERCASE and lowercase. Enter these elements as shown.	Enter sqlplus to open SQL*Plus. The password is specified in the orapwd file. Back up the datafiles and control files in the /disk1/oracle/dbs directory. The department_id, department_name, and location_id columns are in the hr.departments table. Set the QUERY_REWRITE_ENABLED initialization parameter to true. Connect as oe user. The JRepUtil class implements these methods.
<i>lowercase italic monospace (fixed-width) font</i>	Lowercase italic monospace font represents placeholders or variables.	You can specify the <i>parallel_clause</i> . Run <i>Uold_release</i> .SQL where <i>old_release</i> refers to the release you installed prior to upgrading.

## Conventions in Code Examples

Code examples illustrate SQL, PL/SQL, SQL\*Plus, or other command-line statements. They are displayed in a monospace (fixed-width) font and separated from normal text as shown in this example:

```
SELECT username FROM dba_users WHERE username = 'MIGRATE';
```

The following table describes typographic conventions used in code examples and provides examples of their use.

Convention	Meaning	Example
[ ]	Brackets enclose one or more optional items. Do not enter the brackets.	DECIMAL ( <i>digits</i> [ , <i>precision</i> ])
{ }	Braces enclose two or more items, one of which is required. Do not enter the braces.	{ENABLE   DISABLE}
	A vertical bar represents a choice of two or more options within brackets or braces. Enter one of the options. Do not enter the vertical bar.	{ENABLE   DISABLE} [COMPRESS   NOCOMPRESS]

Convention	Meaning	Example
...	Horizontal ellipsis points indicate either: <ul style="list-style-type: none"> <li>That we have omitted parts of the code that are not directly related to the example</li> <li>That you can repeat a portion of the code</li> </ul>	<pre>CREATE TABLE ... AS subquery;  SELECT col1, col2, ... , coln FROM employees;</pre>
.	Vertical ellipsis points indicate that we have omitted several lines of code not directly related to the example.	<pre>SQL&gt; SELECT NAME FROM V\$DATAFILE; NAME ----- /fsl/dbs/tbs_01.dbf /fsl/dbs/tbs_02.dbf . . . /fsl/dbs/tbs_09.dbf 9 rows selected.</pre>
Other notation	You must enter symbols other than brackets, braces, vertical bars, and ellipsis points as shown.	<pre>acctbal NUMBER(11,2); acct      CONSTANT NUMBER(4) := 3;</pre>
<i>Italics</i>	Italicized text indicates placeholders or variables for which you must supply particular values.	<pre>CONNECT SYSTEM/system_password DB_NAME = database_name</pre>
UPPERCASE	Uppercase typeface indicates elements supplied by the system. We show these terms in uppercase in order to distinguish them from terms you define. Unless terms appear in brackets, enter them in the order and with the spelling shown. However, because these terms are not case sensitive, you can enter them in lowercase.	<pre>SELECT last_name, employee_id FROM employees; SELECT * FROM USER_TABLES; DROP TABLE hr.employees;</pre>
lowercase	Lowercase typeface indicates programmatic elements that you supply. For example, lowercase indicates names of tables, columns, or files.  <b>Note:</b> Some programmatic elements use a mixture of UPPERCASE and lowercase. Enter these elements as shown.	<pre>SELECT last_name, employee_id FROM employees; sqlplus hr/hr CREATE USER mjones IDENTIFIED BY ty3MU9;</pre>

## Conventions for Windows Operating Systems

The following table describes conventions for Windows operating systems and provides examples of their use.

Convention	Meaning	Example
Choose Start >	How to start a program.	To start the Database Configuration Assistant, choose Start > Programs > Oracle - HOME_NAME > Configuration and Migration Tools > Database Configuration Assistant.

Convention	Meaning	Example
File and directory names	File and directory names are not case sensitive. The following special characters are not allowed: left angle bracket (<), right angle bracket (>), colon (:), double quotation marks ("), slash (/), pipe ( ), and dash (-). The special character backslash (\) is treated as an element separator, even when it appears in quotes. If the file name begins with \\, then Windows assumes it uses the Universal Naming Convention.	c:\winnt\"system32 is the same as C:\WINNT\SYSTEM32
C:\>	Represents the Windows command prompt of the current hard disk drive. The escape character in a command prompt is the caret (^). Your prompt reflects the subdirectory in which you are working. Referred to as the <i>command prompt</i> in this manual.	C:\oracle\oradata>
Special characters	The backslash (\) special character is sometimes required as an escape character for the double quotation mark (") special character at the Windows command prompt. Parentheses and the single quotation mark (') do not require an escape character. Refer to your Windows operating system documentation for more information on escape and special characters.	C:\>exp scott/tiger TABLES=emp QUERY=\"WHERE job='SALESMAN' and sal<1600\" C:\>imp SYSTEM/password FROMUSER=scott TABLES=(emp, dept)
HOME_NAME	Represents the Oracle home name. The home name can be up to 16 alphanumeric characters. The only special character allowed in the home name is the underscore.	C:\> net start OracleHOME_NAME_TNSListener

Convention	Meaning	Example
<i>ORACLE_HOME</i> and <i>ORACLE_BASE</i>	<p>In releases prior to Oracle8i release 8.1.3, when you installed Oracle components, all subdirectories were located under a top level <i>ORACLE_HOME</i> directory. For Windows NT, the default location was C:\orant.</p> <p>This release complies with Optimal Flexible Architecture (OFA) guidelines. All subdirectories are not under a top level <i>ORACLE_HOME</i> directory. There is a top level directory called <i>ORACLE_BASE</i> that by default is C:\oracle. If you install the latest Oracle release on a computer with no other Oracle software installed, then the default setting for the first Oracle home directory is C:\oracle\orann, where <i>nn</i> is the latest release number. The Oracle home directory is located directly under <i>ORACLE_BASE</i>.</p> <p>All directory path examples in this guide follow OFA conventions.</p> <p>Refer to <i>Oracle Database Platform Guide for Windows</i> for additional information about OFA compliances and for information about installing Oracle products in non-OFA compliant directories.</p>	Go to the <i>ORACLE_BASE\ORACLE_HOME\rdms\admin</i> directory.

---

# Introduction

Oracle Application Server Adapter for IMS/TM (OracleAS Adapter for IMS/TM) enables you to connect Oracle Application Server to an Information Management System-Transaction Management (IMS/TM) system. This chapter provides an overview of the features and architecture of OracleAS Adapter for IMS/TM.

This chapter contains the following sections:

- [OracleAS Adapter for IMS/TM Overview](#)
- [OracleAS Adapter for IMS/TM Architecture](#)

## OracleAS Adapter for IMS/TM Overview

IMS/TM is a high-performance transaction management system that is part of the IBM IMS product family.

The application components in IMS/TM are executable programs called transactions. These programs are typically written in COBOL but may possibly be written in other languages, such as PL/I, C and even Java. There are several types of IMS/TM programs including MPPs (Message Processing Programs) and BMP (Batch Message Processing Programs).

IMS/TM transaction are invoked using an API called OTMA (Open Transaction Manager Access) as well as through 3270 terminals. IMS/TM transactions are built around an input message-output message concept with a special layer (MFS) translating the message to the screen and back, for a user interface.

In addition to OTMA, there is also an IMS/TM transaction gateway that enables TCP/IP access to IMS/TM transactions.

OracleAS Adapter for IMS/TM includes the following features:

- Captures and maintains a metadata schema for IMS/TM by importing COBOL copybooks and transforming them into mapping definitions for Oracle Connect on the OS/390 or z/OS Series platform and by associating the data structures with specific physical files.
- Utilizes an enterprise application integration (EAI) model. Users of a requesting application can model the interactions that they want implemented, specifying what each interaction does, when it occurs, and the inputs and outputs expected for each interaction.
- Provides access to MPP based IMS/TM transactions. Each OracleAS Adapter for IMS/TM outbound interaction is mapped to a specific IMS/TM transaction.
- Maps data structures for facilitating access to IMS/TM transactions from within OracleAS.

- Supports two-phase commit and can fully participate in a distributed transaction.

---

**Note:** To use OracleAS Adapter for IMS/TM with 2PC, you must have RRS installed and configured.


---

## OracleAS Adapter for IMS/TM Architecture

OracleAS adapter includes the following components:

- J2CA 1.0 IMS/TM adapter: The J2CA IMS/TM adapter is a standard resource adapter that is compliant with J2EE Connector Architecture, providing J2EE components connectivity.
- Oracle Connect: Oracle Connect runs on the legacy system and handles requests from the J2CA 1.0 IMS/TM adapter, that runs within Oracle Application Server Containers for J2EE (OC4J).
- Oracle Studio: Oracle Studio is the configuration tool for Oracle Connect. Configuration tasks using Oracle Studio are performed on a Windows platform. Oracle Studio uses perspectives that enables you to generate specific information necessary to model OracleAS Adapter for IMS/TM.

The following figure illustrates the components of OracleAS Adapter for IMS/TM:



---

**Note:** For a comprehensive description of the integration adapter architecture, see the following Oracle documentation:

*Oracle Application Server Adapter Concepts Guide*

---

## Integration Flow from Oracle Application Server to a Legacy Application

The J2CA 1.0 IMS/TM adapter converts the J2CA interaction invocation received from an application client to the XML format and passes the XML format to Oracle Connect on the legacy server. The daemon listens for the request coming from the J2CA 1.0 IMS/TM adapter client and assigns a server process to handle the request. The properties of the server process, such as connection pooling requirements, are defined by a workspace definition within the daemon. The server process includes an instance of the application engine, which converts the XML format into native structures understandable by IMS/TM and passes the converted XML to the back-end adapter. The back-end adapter builds an interaction based on the metadata for the back-end

adapter stored in the repository and the incoming converted XML, and passes it to the legacy application to be executed. The results of the execution are passed back to the application engine, using the back-end adapter, where these results are converted to XML and passed back to the client.





---

# Installing and Configuring OracleAS Adapter for IMS/TM

---

This chapter describes how to install Oracle Connect and Oracle Studio from the CD-ROM and how to configure Oracle Connect using Oracle Studio.

---

**Note:** In addition to the installation procedures described in this chapter, the J2CA 1.0 IMS/TM adapter must be installed with Oracle Application Server. Installing the J2CA 1.0 IMS/TM adapter is described in *Oracle Application Server Adapter Installation Guide*.

---

This chapter includes the following sections:

- [Preinstallation Tasks](#)
- [Installing Oracle Connect on an IBM OS/390 or z/OS Series Platform](#)
- [Updating an Existing Oracle Connect Installation with IMS/TM](#)
- [Installing Oracle Studio](#)
- [Configuring Oracle Connect](#)

## Preinstallation Tasks

Before installing OracleAS Adapter for IMS/TM, ensure that your computer meets the following requirements:

- [IBM OS/390 or z/OS Hardware and Software Requirements](#)
- [Windows Hardware and Software Requirements](#)

## IBM OS/390 or z/OS Hardware and Software Requirements

This section describes the following requirements for installing Oracle Connect on an IBM OS/390 or z/OS platform:

- [Hardware Requirements](#)
- [Software Requirements](#)

### Hardware Requirements

The following table summarizes the hardware requirements for Oracle Connect.

Hardware Component	Requirements
Processor	An IBM S/390 computer
Memory	The minimum requirement is 4MB for each connection. A connection is defined as a connection to a server process or daemon. The actual memory requirement depends on such things as the size of the database and the number of databases accessed.
CD-ROM Drive	An internal or external CD-ROM drive
Disk Space (3380 and 3390 disks)	150 cylinders

### Software Requirements

The following table summarizes the software requirements for Oracle Connect.

Software Component	Requirements
Operating System	IBM OS/390 V2R5 or higher Or IBM z/OS Series V1R0 or higher
IMS/TM TP Monitor	V6R1 or higher
Oracle Application Server	OracleApplication Server 10g (10.1.2.0.1)

## Windows Hardware and Software Requirements

This section describes the following requirements for installing Oracle Studio:

- [Hardware Requirements](#)
- [Software Requirements](#)

### Hardware Requirements

The following table summarizes the hardware requirements for Oracle Studio.

Hardware Component	Requirements
Processor	An Intel or 100% compatible personal computer (PC), based on a Pentium processor
Memory	256 MB RAM
CD-ROM Drive	An internal or external CD-ROM drive
Disk Space for Oracle Studio	100MB free disk space

### Software Requirements

The following table summarizes the software requirements for Oracle Studio.

Software Component	Requirements
Operating System	Microsoft Windows 2000 with service pack 2 or higher, or Microsoft Windows XP, or Microsoft Windows 2003
Microsoft	Network transport protocol software, TCP/IP, included with Microsoft Windows

## Installing Oracle Connect on an IBM OS/390 or z/OS Series Platform

---

**Note:** If you have an Oracle Connect back-end adapter already installed on the IBM OS/390 or z/OS platform, then follow the instructions described in ["Updating an Existing Oracle Connect Installation with IMS/TM"](#) on page 2-12.

The other back-end adapters that run on an IBM OS/390 or z/OS platform are:

- OracleAS Adapter for CICS
  - OracleAS Adapter for IMS/DB
  - OracleAS Adapter for VSAM
- 

This section explains how to install Oracle Connect from the CD-ROM. This section includes the following:

- [Installation Worksheet](#)
- [Preinstallation Instructions](#)
- [Installing the Kit](#)
- [Installation Instructions](#)
- [Postinstallation Instructions](#)

### Installation Worksheet

Verify that you have all the information detailed in the following installation worksheets, so you can refer to it during the configuration process.

**Table 2–1 Preinstallation Information**

Topic	Required Information	Default	Comment
General	Operating system	-	OS/390 V2R5 or higher, or z/OS Series V1R0 or higher
-	Disk space	-	150 cylinders
-	Memory	-	The minimum requirement is 4MB for each connection. A connection is defined as a connection to a server process or daemon. The actual memory requirement depends on such things as the size of the database and the number of databases accessed.
-	Installation high-level qualifier	OCL1012	-
-	Volume	-	-
-	Unit	3390	SMS only: unit where SMS resides.
-	Output class	A	-
-	JCL job card	-	An optional card (up to 6 lines) to replace the prefix job (entered as it will appear in the job)
-	ISPF load library name	ISP.SISPLOAD	-

**Table 2–2 Required Permissions**

Permission
Permission to define an APF-authorized library
Permission to write to an active <code>proclib</code> , such as <code>user.proclib</code>
Permission to update the security manager, such as RACF
Optionally, permission to specify an output class for Oracle Connect output

**Table 2–3 Installation Checklist**

Step	Comment/Outputs
tso profile prefix	Ensures that the user name is not used as part of the dataset name allocated in the next steps
Allocate dataset: {HLQ}.TRANSMIT.KIT	130 tracks (3390), format=FB, record length=80, block size=3120
Allocate dataset: {HLQ}.TRANSMIT.LOAD	420 tracks (3390), format=FB, record length=80, block size=3120
Copy files to OS/390 (or z/OS)	FTP using binary mode
RECEIVE INDSNAME('{HLQ}.TRANSMIT.KIT')	-
da('{HLQ}.TRANSMIT.LIB') UNIT(unit) VOLUME(volume)	-
EX {HLQ}.TRANSMIT.LIB(PREPARE)	Successful MAXCC is 0, 4 or 8 BUILDKIT.SRC and BUILDKIT.LOAD created
EX {HLQ}.BUILDKIT.SRC(NAVINST)	Successful MAXCC is 0 or 4

## Preinstallation Instructions

Before starting the installation, ensure that the following information is available:

- The output class for the installation output if you do not want to use the default value, which is A.
- If you use SMS to manage all datasets, then you cannot provide unit and volume information, the unit where SMS resides.

Before starting the installation, ensure that you have the following permissions:

- Permission to define an APF-authorized library.
- Permission to write to an active `proclib`, such as `user.proclib`.
- Permission to update the security manager, such as RACF.

---

**Note:** Optionally, ensure that you have permission to specify an output class for Oracle Connect output. Assigning a device that is set on `HOLD` prevents the loss of log information when Oracle Connect started tasks finish.

---

Oracle Connect for the IBM OS/390 or z/OS platform is contained in the following datasets:

- OCL1012.TRANSMIT.KIT
- OCL1012.TRANSMIT.LOAD

These datasets are provided on a CD-ROM in the following directory:

- Oracle\_Connect\IMSTM\_Legacy\_Adapter

## Installing the Kit

Perform the following steps on the mainframe:

1. Run the following command:

```
tso profile noprefix
```

The user name will not be used as part of the dataset name. On some systems this is the default.

2. Allocate datasets with the following space for each of these files:

- OCL1012.TRANSMIT.KIT = 130 tracks (3380 and 3390 disks)
- OCL1012.TRANSMIT.LOAD = 420 tracks (3380 and 3390 disks)

For each dataset: RECFM=FB and LRECL=80. The block size is 3120.

3. Using FTP, copy OCL1012.TRANSMIT.KIT and OCL1012.TRANSMIT.LOAD in the binary mode from the installation CD to the mainframe. You can replace the OCL1012 high-level qualifier to any qualifier you want.

## Installation Instructions

Perform the following steps to install Oracle Connect:

1. Run the following command at the TSO prompt:

```
RECEIVE INDSNAME('nnn.TRANSMIT.KIT')
```

Where *nnn* represents the high-level qualifier you want to assign for the Oracle Connect installation. Assign the high-level qualifier you specified in step 7 of the preinstallation procedure. The default value is OCL1012.

---

**Note:** You can use more than one high-level qualifier (such as ACME.DEV.OCL1012) with the following conditions:

- The total length must be less than or equal to twenty characters.
  - The words *transmit* and *buildkit* cannot be used as high-level qualifiers.
- 

2. Enter the following when prompted for the restore parameters:

```
da('nnn.TRANSMIT.LIB') [UNIT(unit) VOLUME(volume)]
```

This extracts the *nnn.TRANSMIT.LIB* library from the *nnn.TRANSMIT.KIT* kit to the specified unit and volume. If a unit and volume are not specified, then the library is extracted to the current unit and volume.

3. Run the PREPARE member of the *nn.TRANSMIT.LIB* library:

```
ex PREPARE
```

Follow the instructions in the Response column in [Table 2-4](#) for each entry in the Screen column.

**Table 2–4 Installation Prepare Job Prompts and Responses**

Screen	Response
DO YOU WANT TO USE SMS MANAGED STORAGE FOR THIS INSTALLATION Y/N [N]:	If you want to manage the storage using SMS, then answer Y, otherwise answer N.
ENTER THE STORCLASS FOR INSTALLATION TEMP DATASETS [ ]:	This prompt is displayed only if SMS is used to manage the installation (you answered Y to the first prompt). Enter the storage class
ENTER THE UNIT NAME FOR INSTALLATION TEMP DATASETS [3390]:	If a storage class is not specified, then enter the unit name for temporary datasets used during the installation procedure
ENTER THE VOLUME NAME FOR INSTALLATION TEMP DATASETS:	This prompt is displayed only if SMS is not used to manage the installation (you answered N to the first prompt). The volume name for temporary datasets used during the installation procedure
ENTER THE OUTPUT CLASS FOR INSTALLATION OUTPUT [A] :	Enter the output class only if you do not want the default class used (the default is A)
DO YOU WANT TO USE THE DEFAULT JOB CARD Y/N [Y]	A job card is displayed. If you want to use a replacement card, then it must be entered as it will appear in the job. You can enter up to six lines. Enter a blank card to end input. If you do not enter a card, then the Oracle Connect default card is used.
DO YOU WANT TO PERFORM A MANUAL (M) OR AUTOMATIC (A) INSTALLATION [A]:	If you want to review the JCL used to install Oracle Connect, before it is submitted, then respond M for a manual installation.
PLEASE REVIEW AND SUBMIT FOR EXECUTION THE HLQ.TRANSMIT.LIB(INSTJO)	This prompt is displayed only if a manual installation is requested (you answered M to the previous prompt).

The following libraries are generated:

```
nnn.BUILDKIT.LOAD
nnn.BUILDKIT.SRC
nnn.BUILDKIT.GENDEMO
```

Where nnn is the high-level qualifiers you assigned in step 1.

4. In the `nnn.BUILDKIT.SRC` library, run the NAVINST member:

```
ex NAVINST
```

Follow the instructions in the Response column in [Table 2–5](#) for each entry in the Screen column.

**Table 2–5 Installation Prompts and Responses**

Screen	Response
DO YOU WANT TO USE SMS MANAGED STORAGE FOR THIS INSTALLATION Y/N [N]:	If you want to manage the storage using SMS, then answer Y, otherwise answer N.
THE SOFTWARE WILL BE INSTALLED UNDER THE HIGH LEVEL QUALIFIER THAT YOU WILL CHOOSE. ENTER THE HIGH LEVEL QUALIFIER ["QUALIFIER"]:	The high-level qualifier for the installation (referred to as <i>INSTROOT</i> throughout this guide)  You can use more than one high-level qualifier (such as ACME.DEV.VA10). The total length must be less than or equal to twenty characters. The qualifiers can be the same as the ones used for the installation (see step 1).  The words <i>transmit</i> and <i>buildkit</i> cannot be used as high-level qualifiers.
ENTER THE STORCLASS FOR TEMP DATASETS ['STORCLASS']:	This prompt is displayed only if SMS is used to manage the installation (you answered Y to the first prompt).  Enter the storage class
ENTER THE UNIT NAME FOR INSTALLATION TEMP DATASETS [3390]:	The unit name for temporary datasets used during the installation procedure.
ENTER THE VOLUME NAME FOR INSTALLATION TEMP DATASETS	This prompt is displayed only if SMS is not used to manage the installation (you answered N to the first prompt).  The volume name for temporary datasets used during the installation procedure
PLEASE CONFIRM (YES/NO/QUIT) [YES]:	Confirm the entered details
ENTER THE OUTPUT CLASS FOR INSTALLATION OUTPUT [A :	Enter the output class for Oracle Connect output. Assigning a device that is set on HOLD prevents the loss of log information when the Oracle Connect started tasks finish (the default is A).
DO YOU WANT TO USE THE DEFAULT JOB CARD Y/N [Y]	A job card is displayed. If you want to use a replacement card, then it must be entered as it will appear in the job. You can enter up to six lines. Enter a blank card to end input.  If you do not enter a card, then the Oracle Connect default card is used.
ADDING AND UPDATING ORACLE CONNECT FOR IMS/TM CONFIGURATION ON THIS MACHINE, FROM A REMOTE ORACLE ADMINISTRATION CONSOLE, CAN ONLY BE DONE BY SOMEONE DEFINED AS AN ADMINISTRATOR FOR ORACLE CONNECT ON THIS MACHINE. ENTER A VALID USER NAME FOR AN ORACLE CONNECT ADMINISTRATOR [ALL]:	To manage Oracle Connect on this computer from Oracle Studio, you need to enter a user account of a user who will have administrative authorization, or press Enter to enable any user to administer Oracle Connect on this computer. The administrative rights can be changed from within Oracle Studio after the installation.
DO YOU WANT TO PERFORM A MANUAL (M) OR AUTOMATIC (A) INSTALLATION [A]:	If you want to review the JCL used to install Oracle Connect, before it is submitted, then respond M for a manual installation.
PLEASE REVIEW AND SUBMIT FOR EXECUTION THE DSN1 (INSTJBOR)	This prompt is displayed only if a manual installation is requested (you answered M to the previous prompt).  DSN1 is the dataset name where INSTJBOR is located.

**5. In the *nnn.BUILDKIT.SRC* library, run the IMSTM member:**

ex IMSTM

6. Follow the instructions in the Response column in [Table 2–6](#) for each entry in the Screen column.

**Table 2–6 IMS/TM Adapter-Specific Installation Prompts and Responses**

Screen	Response
ENTER THE ISPF LOAD LIBRARY NAME [ISP.SISPLOAD] :	Enter the ISPF load library name only if you do not want the default
PLEASE CONFIRM (YES/NO/QUIT) [YES] :	Confirm the entered details
ENTER THE OUTPUT CLASS FOR INSTALLATION OUTPUT [A] :	Enter the output class for Oracle Connect output. Assigning a device that is set on HOLD prevents the loss of log information when the Oracle Connect started tasks finish (the default is A).
DO YOU WANT TO USE THE DEFAULT JOB CARD Y/N [Y]	A job card is displayed. If you want to use a replacement card, then it must be entered as it will appear in the job. You can enter up to six lines. Enter a blank card to end input.  If you do not enter a card, then the Oracle Connect default card is used.

The installation is completed. All JCL jobs and REXX procedures are written to the *INSTROOT*.USERLIB library. *INSTROOT* is the high-level qualifier for the installation.

## Postinstallation Instructions

The following postinstallation tasks must be done to work with Oracle Connect:

- [Postinstallation Procedures](#)
- [Starting the Daemon](#)
- [Setting Up Oracle Connect for Reentrancy](#)

### Postinstallation Procedures

Perform the following procedures after completing the installation to configure Oracle Connect.

- Allocate a dataset for *INSTROOT*.DEF.BRANDBIN, using 1 track and with RECFM=VB and LRECL=256. The block size is 6233.

*INSTROOT* is the high-level qualifier where Oracle Connect is installed.

Using FTP, copy the BRANDBIN file, in binary mode, from the Oracle Connect\IMSTM Legacy Adapter directory in the installation CD to the mainframe, to *INSTROOT*.DEF.BRANDBIN.

- Define the LOADAUT library as an APF-authorized library



---

**Note:** To define a DSN as APF-authorized, in the SDSF screen enter the following command:

```
"/setprog apf,add,dsn=INSTROOT.loadaut,volume=vol002"
```

Where `vol002` is the volume where you installed Oracle Connect and `INSTROOT` is the high-level qualifier where Oracle Connect is installed.

If the site uses SMS, then when defining APF-authorization in the SDSF screen, enter the following command:

```
"/setprog apf,add,dsn=INSTROOT.loadaut,SMS"
```

Ensure that the library is APF-authorized, even after an IPL (restart) of the computer.

---

- Move the `INSTROOT.USERLIB(ATTTDAEMN)` and `INSTROOT.USERLIB(ATTSSVR)` members to any active proclib (such as `user.proclib`). `ATTTDAEMN` and `ATTSSVR` are run as started tasks.

If you decide to change the name of the `ATTSSVR` member when you move it to a general high-level qualifier, then change the name specified in the `StartupScript` parameter in the daemon configuration to the new name:

- Run `INSTROOT.USERLIB(NAVCMO)` and enter `EDIT DAEMON IRPCDINI` at the prompt.
- Change the `startupScript` parameter from `ATTSSVR` to the new name for the server:

```
<Workspace name="Navigator"
  startupScript="NEW_NAME"
  serverMode="reusable"
... />
```

- Exit and save the changes.
- Change the following line in the `ATTTDAEMN` script to include the IP address and port of the IBM OS/390 or z/OS platform.

For example, before:

```
// PARM='-B START IRPCDINI'
```

After:

```
// PARM='-B -L ip_address:2252 START IRPCDINI'
```

Where `ip_address` is ip address of the computer, 2252 is the default port for starting the daemon and `IRPCDINI` is the default daemon configuration.

- The `ATTTDAEMN` and `ATTSSVR` started tasks need permission to use an Open Edition TCP/IP stack. The owner must be a user with OMVS segment defined and the OMVS UID should be 0000000000.
- In the security manager, such as RACF, define `ATTTDAEMN` and `ATTSSVR` with a started task class and a general profile that enables the following:
  - Permission to issue master console commands.
  - START authority for the `ATTSSVR` job.

- Access to an Open OS/390 segment (that defines access to TCP/IP OA sockets).
- ALTER authority on datasets under *INSTROOT* to access to read, write, allocate and delete datasets under *INSTROOT*.
- The installation includes a PS, *INSTROOT*.DEF.GBLPARMS, that contains global environment information. This PS is read at startup and the correct software version is used, based on the details provided in the startup task.

If you change the location of this member, then you must also change the relevant cards in the following jobs to the new locations:

- ATTSRVR: Located in an active proclib, such as *user*.proclib
- ATTTDAEMN: Located in an active proclib, such as *user*.proclib
- NAVSQL: Located in *INSTROOT*.USERLIB
- The input during the installation procedure is written to *nnn*.BUILDKIT.SRC(PARS). You can use this file to provide the same inputs if you rerun the installation, where *nnn* is the high-level qualifier you assign for the installation.
- For information about specifying Oracle Connect as the service using port 2552 in the TCP/IP network services file, refer to the TCP/IP documentation.

## Starting the Daemon

Activate *INSTROOT*.USERLIB(ATTDAEMN) as a started task to invoke the daemon. For example, in the SDSF screen enter the following:

```
'/s ATTTDAEMN'
```

Where *INSTROOT* is the high-level qualifier where Oracle Connect is installed.

To submit the daemon as a job, remove comments from the first two lines of the ATTTDAEMN JCL, change the PARM line as described earlier, and run the job using the sub command. The following is a sample ATTTDAEMN JCL.

```
//*ATTTDAEMN JOB 'RR','TTT',MSGLEVEL=(1,1),CLASS=A,
/* MSGCLASS=A,NOTIFY=&SYSUID,REGION=8M
//STEP1 EXEC PGM=IRPCD,
// PARM='-B START IRPCDINI'
/* PARM='-B -L :8883 START'
//STEPLIB DD DSN=INSTROOT.LOADAUT,DISP=SHR
//SYSPRINT DD SYSOUT=A
//GBLPARMS DD DSN=INSTROOT.DEF.GBLPARMS,DISP=SHR
// EXEC PGM=IRPCD,COND=((1,EQ,STEP1),(2,EQ,STEP1)),
// PARM='-KATTTDAEMN START ''INSTROOT.DEF.IRPCDINI'''
//STEPLIB DD DSN=INSTROOT.LOADAUT,DISP=SHR
//SYSPRINT DD SYSOUT=A
//GBLPARMS DD DSN=INSTROOT.DEF.GBLPARMS,DISP=SHR
//SYSDUMP DD DUMMY
```

## Setting Up Oracle Connect to Work Under IMS/TM

To run an IMS transaction, set OTMA (Open Transaction Manager Access), as follows:

1. Install OTMA with OTMA C/I where IMS resides, as OTMA is not automatically installed using the IMS INSTALL/IVP Dialog.
2. During IMS system definition, set the startup parameter in the IMS procedure to OTMA=YES. In addition, set additional OTMA-related parameters such as

GRNAME for the XCF group name and OTMANM for the IMS member name in that XCF group, as in the following example:

```
EDIT      IMS.PROCLIB(DFSPBIV1) - 01.03
command ==>
000082 AOIS =,
000083 GRNAME=IMSATT01,
000084 OTMA=YES,
000085 MAXPST=
000086 OTMANM=
```

### 3. Start the OTMA Callable Interface (C/I).

Add an entry in the program properties table (PPT) for the OTMA C/I initialization program as follows:

- a. Edit the SCHEDxx member of the SYS1.PARMLIB data set by adding the following entry:

```
PPT PGMNAME(DFSYSVIO) /*PROGRAM NAME =DFSYSVIO */
CANCEL /*PROGRAM CAN BE CANCELED */
KEY(7) /*PROTECT KEY ASSIGNED IS 7 */
SWAP /*PROGRAM IS SWAPPABLE */
NOPRIV /*PROGRAM IS NOT PRIVILEGED */
DSI /*REQUIRES DATA SET INTEGRITY */
PASS /*CANNOT BYPASS PASSWORD PROTECTION */
SYST /*PROGRAM IS A SYSTEM TASK */
AFF(NONE) /*NO CPU AFFINITY */
NOPREF /*NO PREFERRED STORAGE FRAMES */
```

- b. To make the SCHEDxx changes take effect, perform one of the following tasks:
  - Re-IPL the system.
  - Issue the SET SCH= command.
- c. Edit and submit the following JCL procedure to run DFSYSVIO:

```
//OTMAINIT PROC RGN=3000K,SOUT=A,
//PARM1=
//*
//IEFPROC EXEC PGM=DFSYSVIO,
//REGION=&RGN
//*
//STEPLIB DD DISP=SHR,UNIT=SYSDA,
//DSN=IMSVS.RESLIB
//*
//SYSPRINT DD SYSOUT=&SOUT
//SYSUDUMP DD SYSOUT=&SOUT
//*
```

4. Run DFSYSVIO after the IPL, to initialize the OTMA C/I.
5. Copy *INSTROOT.LOAD* (ATYDBDC) to an IMS/TM program library, such as IMS.PGMLIB.

## Setting Up Oracle Connect for Reentrancy

All Oracle Connect load modules are reentrant to enable subtasking. Therefore, move *INSTROOT.LOAD* to the Link Pack Area (LPA).

Where *INSTROOT* is the high-level qualifier where Oracle Connect is installed.

Using the LPA reduces real storage usage, because everyone shares the LPA copy, and fetch time.

---

**Note:** If you intend using impersonation, so that you can run in a security context that is different than the context of the process that owns the server, then do the following:

- Place the `INSTROOT.LOAD(ATYSVCW)` member in an APF-authorized library outside the LPA.
- Change the `ATTSRVR` member (located in the active proclib), by adding the following to the `STEPLIB` list:

```
// DD DSN=apf_library,DISP=SHR
```

Where `apf_library` is the APF-authorized library outside the LPA directory where the `ATYSCVW` member was moved.

---

## Updating an Existing Oracle Connect Installation with IMS/TM

Verify that you have all the information detailed in the following installation worksheets. You can refer to it during the configuration process.

**Table 2–7 Preinstallation Information**

Topic	Required Information	Default	Comment
CICS	CICS EXCI load library name	CICS.CICS.SDFHEXCL	To access IMS/DB or VSAM data under CICS

**Table 2–8 Required Permissions**

Permission
Permission to read the CICS EXCI library (when accessing IMS/DB or VSAM data under CICS)

In the `nnn.BUILDKIT.SRC` library, run the `CUSTOCL` member:

```
ex CUSTOCL
```

Follow the instructions in the Response column in [Table 2–9](#) for each entry in the Screen column.

**Table 2–9 IMS/TM Adapter Installation Prompts and Responses**

Screen	Response
DO YOU WANT ORACLE CONNECT FOR LEGACY ADAPTER TO WORK WITH IMS/DB (YES/NO) [YES] :	Answer YES to this prompt if you have Oracle Connect for IMS/DB already installed.
ENTER DBD LIBRARY NAME [IMS.DBDLIB] :	If you responded YES to working with IMS/DB, then enter the library where database definition (DBD) files are located.
ENTER PSB LIBRARY NAME [IMS.PSBLIB] :	If you responded YES to working with IMS/DB, then enter the library where Program Specification Blocks (PSBs) are located.
ENTER YOUR PSB NAME [HOSPPSB] :	If you responded YES to working with IMS/DB, then enter the name of the PSB file to use.
PLEASE CONFIRM (YES/NO/QUIT) [YES]:	If you responded YES to working with IMS/DB, then confirm the entered details.

**Table 2–9 (Cont.) IMS/TM Adapter Installation Prompts and Responses**

Screen	Response
DO YOU WANT ORACLE CONNECT FOR LEGACY ADAPTER TO WORK WITH IMS/DB UNDER CICS (YES/NO) [NO]:	If you want to access IMS/DB data under CICS, using OracleAS Adapter for IMS/DB, then respond YES.
ENTER THE CICS EXCI LOAD LIBRARY NAME [CICSTS13.CICS.SDFHEXCI]:	If you responded YES to working with IMS/DB under CICS, then enter the CICS EXCI load library name only if you do not want the default.
PLEASE CONFIRM (YES/NO/QUIT) [YES]:	If you responded YES to working with IMS/DB under CICS, then confirm the entered details.
DO YOU WANT ORACLE CONNECT FOR LEGACY ADAPTER TO WORK WITH CICS APP ADAPTER (YES/NO) [YES]:	Answer YES to this prompt
ENTER THE CICS EXCI LOAD LIBRARY NAME [CICSTS13.CICS.SDFHEXCI]:	Enter the CICS EXCI load library name only if you do not want the default.
PLEASE CONFIRM (YES/NO/QUIT) [YES]	Confirm the entered details
THE VSAM DRIVER IS INSTALLED AUTOMATICALLY. DO YOU ALSO WANT ORACLE CONNECT FOR LEGACY ADAPTER TO WORK WITH VSAM UNDER CICS (YES/NO) [NO]:	Answer YES to this prompt if you have Oracle Connect for VSAM already installed and you want to access VSAM data under CICS.
ENTER THE CICS EXCI LOAD LIBRARY NAME [CICSTS13.CICS.SDFHEXCI]:	If you responded YES to working with VSAM under CICS, then enter the CICS EXCI load library name only if you do not want the default.
PLEASE CONFIRM (YES/NO/QUIT) [YES]:	If you responded YES to working with VSAM under CICS, then confirm the entered details.
ENTER THE ISPF LOAD LIBRARY NAME [ISP.SISPLOAD]:	Enter the ISPF load library name only if you do not want the default.
PLEASE CONFIRM (YES/NO/QUIT) [YES]:	Confirm the entered details
ENTER THE OUTPUT CLASS FOR INSTALLATION OUTPUT [A]:	Enter the output class for Oracle Connect output. Assigning a device that is set on HOLD prevents the loss of log information when the Oracle Connect started tasks finish (the default is A).
DO YOU WANT TO USE THE DEFAULT JOB CARD Y/N [Y]	A job card is displayed. If you want to use a replacement card, then it must be entered as it will appear in the job. You can enter up to six lines. Enter a blank card to end input.  If you do not enter a card, then the Oracle Connect default card is used.

The installation is completed. All JCL jobs and REXX procedures are written to the *INSTROOT*.USERLIB library. *INSTROOT* is the high-level qualifier for the installation.

After completing the installation, perform postinstallation tasks, as described in ["Postinstallation Instructions"](#) on page 2-8.

## Installing Oracle Studio

This section explains how to install Oracle Studio from the CD-ROM.

---

---

**Note:** If Oracle Studio is already installed because you are also using another legacy adapter, then you do not need to reinstall it.

The other legacy adapters are:

- OracleAS Adapter for Tuxedo
  - OracleAS Adapter for CICS
  - OracleAS Adapter for IMS/DB
  - OracleAS Adapter for VSAM
- 
- 

## Installing Oracle Studio from the CD-ROM

Assuming that the CD-ROM drive is D:, the installation file is located in the D:\Oracle\_Studio directory. Install Oracle Connect from the CD-ROM by running the self-extracting executable installation file, OSL904-win32.exe.

---

---

**Note:** If you are installing Oracle Studio on a Windows XP computer, you cannot specify a logical drive as the Destination folder for the installation.

---

---

## Configuring Oracle Connect

All modeling of Oracle Connect is performed using Oracle Studio. To use Oracle Studio, you first configure it to enable access to the IBM OS/390 or z/OS platform where IMS/TM runs.

To configure Oracle Connect, refer to the following sections:

- [Setting Up the IBM OS/390 or z/OS Platform in Oracle Studio](#)
- [Securing Access to Oracle Connect](#)
- [Modeling Interactions for OracleAS Adapter for IMS/TM](#)
- [Viewing the XML Schema](#)
- [Creating XML Schemas](#)

---

---

**Note:** The following tasks assume you have permission to access the IBM OS/390 or z/OS platform and that the Oracle Connect daemon is running on this computer.

Check with the system administrator to ensure these requirements are fulfilled.

---

---

## Setting Up the IBM OS/390 or z/OS Platform in Oracle Studio

Perform the following steps to configure the IBM OS/390 or z/OS, using Oracle Studio:

1. From the **Start** menu, select **Programs, Oracle**, and then select **Studio**.
2. Right-click **Machines** in the **Configuration Explorer** and select **Add Machine**. The Add Machine screen is displayed.


3. Enter the name of the computer you want to connect to, or click **Browse** to select the computer from the list of computers that is displayed and which use the default port (2552).
4. Specify the username and password of the user who was specified as the administrator when Oracle Connect was installed.

---

**Note:** Selecting **Anonymous connection** enables anyone having access to the computer to be an administrator.

---

The Add Machine screen is shown in the following figure.



5. Click **Finish**.

The computer is displayed in the **Configuration Explorer**.

## Securing Access to Oracle Connect

Oracle Studio includes mechanisms to secure access to Oracle Connect both during modeling and during run time.

During modeling the following security mechanisms can be applied:

- [Setting Password Access to Oracle Studio](#)
- [Specifying Users with Administrative Rights](#)

During run time client access to Oracle Connect is provided by the user profile:

- [Setting Up Run-time User Access to the IBM OS/390 or z/OS Platform](#)


### Setting Password Access to Oracle Studio

Initially, any operation performed using Oracle Studio does not require a password. You can set a password so that the first operation that involves accessing the server from Oracle Studio requires a password to be entered.

Perform the following steps:

1. From the **Start** menu, select **Programs, Oracle** and then select **Studio**. Oracle Studio opens.
2. Select **Window** from the menu bar and then select **Preferences**.

The Preferences screen is displayed, as shown in the following figure:



3. Select the **Studio** node.
4. Click **Change master password** to display the Change master password screen.
5. In the Change master password screen, leave the **Enter current master password** field empty and type a new master password.
6. Confirm the password.
7. Click **OK**.

### Specifying Users with Administrative Rights

By default, only the user who was specified during the installation as an administrator has the authorization to modify settings on that computer from Oracle Studio. This user can then authorize other users to make changes or to view the definitions for a selected computer. Adding a computer to Oracle Studio is described in ["Setting Up the IBM OS/390 or z/OS Platform in Oracle Studio"](#) on page 2-14.

---


**Note:** The default during installation is to enable all users to be administrators.

---

Perform the following steps to specify a user with administrative rights:

1. From the **Start** menu, select **Programs, Oracle**, and then select **Studio**. Oracle Studio is displayed.
2. Right-click the computer in the **Configuration Explorer** and select **Administration Authorization**. The Administration Authorization screen is displayed, as shown in the following figure:






3. Add users or groups of users by clicking **Add User** or **Add Group** for the relevant sections. The user or group that is added must be recognized as a valid user or group for the computer.

Once a name has been added to a section, only the user or group who logs on with that user name has the relevant authorization.


### Setting Up Run-time User Access to the IBM OS/390 or z/OS Platform

During run time, client access to Oracle Connect is provided by the user profile. A user profile contains name and password pairs that are used to access a computer, data source or application at run time, when anonymous access is not allowed.

1. In the Configuration Explorer, expand the node of the computer for which you want to set the user name and password.
2. Expand the **Users** node.
3. Right-click the **NAV** user profile and select **Edit User**. The User Editor pane is displayed, as shown in the following figure:



4. In the User editor, click **Add** to display the Add Authenticator screen.
5. Select **Remote Machine** from the **Resource type** list as shown in the following figure:



6. Enter the name of the IBM OS/390 or z/OS computer defined in Oracle Studio.
7. Enter the name and password used to access the computer and confirm the password.
8. Click **OK**.

## Modeling Interactions for OracleAS Adapter for IMS/TM

Modeling interactions for OracleAS Adapter for IMS/TM involves defining an Oracle Connect back-end adapter using Oracle Studio. All the definitions specified in Oracle Studio are written to the IBM OS/390 or z/OS platform.

This section contains the following:

- [Setting Up an Oracle Connect Adapter](#)
- [Generating Outbound Interactions](#)
- [Generating Inbound Interactions](#)

## Setting Up an Oracle Connect Adapter

To work with the Oracle Connect, you need to set up an adapter definition on the IBM OS/390 or z/OS platform to handle the interactions to and from an IMS/TM transaction. You use Oracle Studio to specify these definitions.

Perform the following steps:


1. From the **Start** menu, select **Programs, Oracle**, and then select **Studio**.
2. In the Configuration Explorer, expand the node of the computer defined in ["Setting Up the IBM OS/390 or z/OS Platform in Oracle Studio"](#) on page 2-14.
3. Expand the **Bindings** node. The binding configurations available on this computer are listed.
4. Expand the **NAV** binding node. The NAV binding configuration includes branches for data sources and adapters that are located on the computer.
5. Right-click **Adapters** and select **New Adapter** to open the New Adapter wizard.
6. Enter a name for the back-end adapter.

---

**Note:** The word *event* is a reserved word and cannot be used when naming an adapter.

---

7. Select **IMS/TM** as the back-end adapter type from the **Type** list as shown in the following figure:



8. Select **Events**.
9. Click **Finish**. The back-end adapter is added to the list and the definition opens for editing.

---

**Note:** Other adapters that are displayed in the **Type** list are not supported with the version of Oracle Connect installed at the site.

---

10. Select the Properties tab and change any of the properties for the adapter, as required.

The Properties tab is shown in the following figure:

[illegible]

The Properties tab comprises fields, as listed in the following table:

Property	Description
cachLastTpipe	Cache the last transaction pipe used.
cacheXcfConnection	Cache the XCF connection information.
maxSessions	The maximum number of sessions allowed. The default value is 5.
racfGroupId	The RACF facility group identification.
racfUserId	The RACF facility user identification.
tpipePrefix	The transaction pipe prefix used to associate between the transaction and the transaction pipe it is using. The default is ATTU.
xcfClient	The Cross System Coupling Facility client name.
xcfGroup	The Cross System Coupling Facility collection of XCF members to which the connection belongs. A group may consist of up to eight characters, and may span between multiple systems.
xcflmsMember	The Cross System Coupling Facility group member.

## Generating Outbound Interactions

Oracle Connect requires metadata describing the adapter interactions, including the structures used to pass information to and from the adapter.

If COBOL copybooks describing the adapter input and output structures are available, then you can import the adapter definition using the Metadata Import wizard in Oracle Studio Design perspective to generate interaction metadata. If the metadata is provided in a number of COBOL copybooks, with different filter settings (such as whether the first six columns are ignored or not), then you first import the metadata

from copybooks with the same settings and later import the metadata from the other copybooks.


If COBOL copybooks describing the input and output structures are not available, then you need to manually define the metadata.

The following information is required during the import procedure:

- The COBOL copybooks: These are copied to the computer running Oracle Studio as part of the import procedure.
- The names of the IMS/TM transactions to be executed through the application adapter.

Use the Metadata Import procedure to generate interaction metadata, as follows:

1. In the Configuration explorer, right-click the IMS/TM back-end adapter defined in ["Setting Up an Oracle Connect Adapter"](#) on page 2-19.
2. Select **Edit metadata**, to display the Metadata tab, with the IMS/TM back-end adapter displayed under the **Adapters** list.
3. Right-click the **Imports** node and select **New Import**. The New Metadata Import screen is displayed.
4. Enter a name for the import. The name can contain letters and numbers and the underscore character only.
5. Select **ImsTm Import Manager** from the **Import type** list as shown in the following figure:




6. Click **Finish**. The Metadata Import wizard is displayed.
7. Click **Add**. The Select Resources screen is displayed, which provides the option to select files from the local computer or copy the files from another computer.
8. If the files are on another computer, then right-click **My FTP Sites** and select **Add**. Optionally, double-click **Add FTP site**. The Add FTP Site screen is displayed.
9. Enter the server name or IP address where the COBOL copybooks reside and enter a valid username and password to access the computer (if anonymous access is used, then click **Anonymous connection**) then click **OK**.

The FTP site is added to the list of available sites as shown in the following figure:

---

**Note:** The selected server is accessed using the username as the high-level qualifier, enabling you to browse and transfer files.

---



10. Right-click the computer and select **Set Transfer Type**. Enter the transfer type (ASCII or BINARY) and click **OK**.
11. Expand the list of the added site until you find the necessary COBOL files. To change the high-level qualifier, right-click the computer and select **Change Root Directory**. Enter the new high-level qualifier enclosed in quotes, and click **OK**.
12. Select the required COBOL copybook file or files and click **Finish**. The selected file or files are displayed in the Metadata Import wizard.

---

**Note:** You can import the metadata from one COBOL copybook and later add to this metadata by repeating the import procedure using different COBOL copybooks.

The format of the COBOL copybooks must be identical. That is, you cannot import a COBOL copybook that uses the first six columns with a COBOL copybook that ignores the first six columns. In this type of case you **must** repeat the import procedure.

---

13. Click **Next**. The Apply Filters screen is displayed, as shown in the following figure.

Property	Value
<input checked="" type="checkbox"/> cobolFilter	
<input checked="" type="checkbox"/> compilerSourceSettings	
COMP_6 switch (for MICROFOCUS compiler source only)	COMP-6'2'
Compiler source	Default / Not known / Other
Storage mode (for MICROFOCUS compiler source only)	NOIBMCOMP
Ignore after column 72	true
Ignore first 6 columns	false
Prefix nested columns	true
Replace hyphens (-) in record and field names with underscores...	true
<input checked="" type="checkbox"/> template	
Case sensitive	false
Find	
Replace with	

14. Apply filters to the copybooks, as needed.

The following table lists the available filters:

Filter	Description
COMP_6 switch	The MicroFocus COMP-6 compiler directive. Specify either COMP-6'1' to treat COMP-6 as a COMP data type or COMP-6'2' to treat COMP-6 as a COMP-3 data type.
Compiler source	The compiler vendor.
Storage mode	The MicroFocus Integer Storage Mode. Specify either NOIBMCOMP for byte storage mode or IBMCOMP is for word storage mode.
Ignore after column 72	Ignores columns 73 to 80 in the COBOL copybook.
IgnoreFirst6	Ignores the first six columns in the COBOL copybook.
Replace hyphens (-) in record and field names with underscores (_)	Replaces all hyphens in either the record or field names in the metadata generated from the COBOL with underscore characters.
Prefix nested columns	Prefix all nested columns with the previous level heading.

Filter	Description
Case sensitive	Specifies whether to be sensitive to the search string case.
Find	Searches for the specified value.
Replace with	Replaces the value specified for Find with the value specified here

15. In the import wizard, click **Next**. The Add Interactions screen is displayed, as shown in the following figure:

**Add Interactions** Step 3 of 5

Add Interactions:

Name	Mode	Input	Output	Description
getCustOrders	sync-send-rece...	CUSTOMERS	ORDERS	

Buttons: Add, Remove

Interaction-Specific Parameters:

Property	Value
transaction	getOrd

Buttons: << Back, Next >>, Finish

16. Click **Add** to add an interaction for the IMS/TM adapter. Provide the information, as listed in the following table:

Parameter	Description
Name	The name of the interaction. You can change the default name specified.
Mode	<p>The interaction mode. You can select one of the following:</p> <ul style="list-style-type: none"> <li>■ sync-send-receive: The interaction sends a request and expects to receive a response. This is the default mode.</li> <li>■ sync-receive: The interaction expects to receive a response</li> <li>■ sync-send: The interaction sends a request and does not expect to receive a response.</li> </ul>



Parameter	Description
Input	<p>Identifies an input record. The input record is the data structure for the interaction. The records generated from the COBOL files specified at the beginning of the procedure are listed. Select the relevant record for the interaction.</p> <p><b>Note:</b> You must specify an input record for each interaction before you can click <b>Next</b>. If the interaction does not require an input record, then the record specified here is ignored.</p>
Output	<p>Identifies an output record. The output record is the data structure for the results of the interaction. The records generated from the files specified at the beginning of the procedure are listed. Select the relevant record for the interaction.</p> <p><b>Note:</b> You must specify an output record for the interaction if the mode is set to sync-send-receive or sync-receive, before you can click <b>Next</b>.</p>
Description	Free text describing the interaction.
Interaction-Specific Parameters	<p>IMS/TM specific parameters:</p> <ul style="list-style-type: none"> <li>■ <b>c</b>: The interaction commit mode.</li> <li>■ <b>maxSegmentSize</b>: The maximum size of the segment. The default value is 32768 (bytes).</li> <li>■ <b>transaction</b>: The name of the transaction that is executed when the interaction is executed. You must specify a transaction name for each interaction.</li> </ul> <p>The <b>maxSegmentSize</b> parameter enables dynamically splitting large messages into smaller segments. Although the default value can be changed, the logic of IMS/TM transaction must correspond accordingly. The transaction must perform a GU call followed by a series of GN calls in order to compile the entire input message. A transaction output message, larger than 32K, is handled by the OTMS C/I interface which performs the task of assembling the output segments into a single buffer.</p>

17. Add as many interactions as necessary and click **Next** to generate the metadata definitions for the adapter.

18. Specify that you want to transfer the metadata from the Windows computer to the IBM OS/390 or z/OS platform and click **Finish**.

The metadata is imported based on the options specified and it is stored on the IBM OS/390 or z/OS platform. An XML representation of the metadata is also generated.

After performing the import, you can view the metadata in Oracle Studio Design perspective Metadata tab. You can also make any fine adjustments to the metadata and maintain it, as necessary.

**See Also:** [Appendix A, "Advanced Tuning of the Metadata"](#) for details about fine tuning the adapter metadata

## Generating Inbound Interactions

Inbound interactions are defined as events in Oracle Studio. When you defined the Oracle Connect for IMS/TM back-end adapter with **Event** selected, an event adapter was defined automatically. The event adapter is defined with the same name as the back-end adapter with the word *event* appended to it. The back-end adapter and the event adapter are linked by Oracle Studio.

You can skip from the adapter definition to the event definition by right-clicking the adapter or event in the Configuration Explorer list and choosing the **Linked Event** or **Linked Adapter** option respectively.

The event adapter requires metadata describing the inbound interactions, including the structure used to pass information.

---


**Note:** The generation of inbound interactions involves similar steps to the steps described to generate outbound interactions.

---

Use the Metadata Import procedure in Oracle Studio to generate interaction metadata, as follows:


1. In the Configuration Explorer, right-click the IMS/TM back-end adapter defined in ["Setting Up an Oracle Connect Adapter"](#) on page 2-19.
2. Select **Linked Event**, to skip to the event adapter.
3. Right-click the event adapter and select **Edit Event**.
4. Click the **Properties** tab to add the names of Oracle Application Server users who can retrieve inbound interactions and OS/390 users who can send inbound interactions.
5. To add Oracle Application Server users, expand the **Routers** node and right-click the users property to add the user.

The Properties tab is shown in the following figure:



6. Enter the name of the Oracle Application Server user in the **Value** column for the item added.
7. To add OS/390 users, expand the **Senders** node and right click the users property to add the user.
8. Enter the name of the OS/390 user in the **Value** column for the item added.
9. Click **Save** to save the changes.
10. Right-click the event adapter in the **Configuration Explorer** and select **Edit metadata**, to display the Metadata tab, with the event adapter displayed under the **Events** list.
11. Right-click the **Imports** node and select **New Import**, to open the New Metadata Import wizard.
12. Enter a name for the import. The name can contain letters and numbers and the underscore character only.
13. Select **Event Queue Import Manager Using Cobol COPYBOOK Input Files** as the import type, and click **Finish**.

The New Import screen is shown in the following figure:



After defining an import type, the metadata import wizard opens in Oracle Studio. COBOL copybooks are used to create the metadata. The import wizard generates record structures, which are used for the record structures for inbound interactions.


14. Click **Add** in the metadata import wizard. The Select Resource screen provides the option to select files from the local computer or copy the files from another computer.
15. If the files are on another computer, then right-click **My FTP Sites** and select **Add**. Optionally, double-click **Add FTP Site**. The Add FTP Site screen is displayed.
16. Enter the server name or IP address where the COBOL copybooks reside and enter a valid username and password to access the computer (if anonymous access is used, then click **Anonymous connection**) then click **OK**. The FTP site is added to the list of available sites.

---

**Note:** The selected server is accessed using the username as the high-level qualifier, enabling you to browse and transfer files.

---

The Select Resource screen is shown in the following figure:



17. Right-click the computer and select **Set Transfer Type**. Enter the transfer type (ASCII or BINARY) and click **OK**.
18. Expand the node of the added site and locate the necessary COBOL files. To change the high-level qualifier, right-click the computer and select **Change Root Directory**. Enter a high-level qualifier enclosed in quotes, and click **OK**.
19. Select the file or files and click **Finish**. The selected file or files are displayed in the metadata import wizard.
20. In the Import wizard, click **Next**.

[illegible]

**21.** Apply filters to the copybooks.

The following table lists the available filters:

Filter	Description
COMP_6 switch	The MicroFocus COMP-6 compiler directive. Specify either COMP-6'1' to treat COMP-6 as a COMP data type or COMP-6'2' to treat COMP-6 as a COMP-3 data type.
Compiler source	The compiler vendor.
Storage mode	The MicroFocus Integer Storage Mode. Specify either NOIBMCOMP for byte storage mode or IBMCOMP is for word storage mode.
Ignore after column 72	Ignores columns 73 to 80 in the COBOL copybook.
IgnoreFirst6	Ignores the first six columns in the COBOL copybook.
Replace hyphens (-) in record and field names with underscores (_)	Replaces all hyphens in either the record or field names in the metadata generated from the COBOL with underscore characters.
Prefix nested columns	Prefix all nested columns with the previous level heading.
Case sensitive	Specifies whether to be sensitive to the search string case.

Filter	Description
Find	Searches for the specified value.
Replace with	Replaces the value specified for Find with the value specified here

22. Click **Next**. The Add Events screen is displayed.

23. Click **Add** to add an event for the IMS/TM adapter. Provide the following information:

Parameter	Description
Name	The name of the event. You can change the default name specified.
Mode	The event mode. You can select the following: <ul style="list-style-type: none"> <li>■ <b>async-send</b>: The event sends a request and does not expect to receive a response.</li> </ul>
Input	Identifies an input record. The input record is the data structure for the event. The records generated from the COBOL files specified at the beginning of the procedure are listed. Select the relevant record for the event.  <b>Note:</b> You must specify an input record for each event before you can click <b>Next</b> . If the interaction does not require an input record, then the record specified here is ignored.
Description	Free text describing the event.

The Add Events screen is shown in the following figure:

**Add Events** Step 3 of 5

Add Events:

Name	Mode	Input	Output	Description
event1	async-send	ORDERS		


Add  
Remove

<< Back   Next >>   Finish

24. Add the required events.

25. Click **Next** to generate the metadata definitions for the adapter.

26. Specify that you want to transfer the data from the Windows computer to the IBM OS/390 or z/OS platform, as shown in the following figure:



27. Click **Finish**.

The metadata is imported based on the options specified and it is stored on the IBM OS/390 or z/OS platform. An XML representation of the metadata is also generated.

After performing the import, you can view the metadata in Oracle Studio Design perspective Metadata tab. You can also make adjustments to the metadata and maintain it, as necessary.

**See Also:** [Appendix A, "Advanced Tuning of the Metadata"](#) for details about fine tuning the adapter metadata.

## Viewing the XML Schema

The XML describing the adapter interactions can be viewed in Oracle Studio Design perspective Metadata Source tab.

## Creating XML Schemas

The XML schema describing the adapter interactions and the input and output records for these interactions are created automatically during the import procedure, as described in ["Generating Outbound Interactions"](#) on page 2-20.



---

## Integrating OracleAS Adapter for IMS/TM with OC4J

To deploy and integrate OracleAS Adapter for IMS/TM with Oracle Application Server Containers for J2EE (OC4J), you need to configure the J2CA 1.0 IMS/TM adapter.

This chapter includes the following sections:

- [Integrating OracleAS Adapter for IMS/TM with OC4J](#)
- [Configuring the J2CA 1.0 IMS/TM Adapter](#)
- [Using the CCI API to Develop Applications](#)
- [Configuring Multiple Adapters](#)
- [Updating Configuration Information](#)

### Integrating OracleAS Adapter for IMS/TM with OC4J

Oracle Application Server provides a complete Java 2 Enterprise Edition (J2EE) environment that executes on the Java virtual computer (JVM) of the standard Java Development Kit (JDK). OC4J is J2EE certified and provides all the J2EE specific containers, APIs, and services. OC4J supports the J2CA 1.0 standard.

J2CA defines standard Java interfaces for simplifying the integration of applications with the EIS. The Oracle adapters are deployed as a resource adapter (RA) within the OC4J container. The contract between the OC4J client application and the resource adapter is defined by the common client interface (CCI). The contract between the OC4J container and the resource adapter is defined by the service provider interface (SPI). The SPI API addresses the connection management, transaction management and the security management. Connection management enables application components to connect to an EIS and leverage any connection pooling provided by the application server. Transaction management enables an application server to use a transaction manager to manage transactions across multiple resource managers. Security management provides authentication, authorization, and secure communication between the J2EE server and the EIS.

**See Also:** *Oracle Application Server Adapter Concepts Guide, Oracle Application Server Containers for J2EE User's Guide, Oracle Application Server Containers for J2EE Services Guide, and Oracle Application Server Containers for J2EE Security Guide.*

## Configuring the J2CA 1.0 IMS/TM Adapter

To connect to the J2CA 1.0 IMS/TM adapter, perform the following steps:

1. Edit the `oc4j-ra.xml` file, which is located at the following path:

```
root\j2ee\home\application-deployment\default\attunity\oc4j-ra.xml
```

Where `root` is the Oracle Application Server root directory.

2. Set the following settings for each connection:

```
<oc4j-connector-factories>
  <connector-factory location=" " connector-name="Oracle Legacy Adapter">
    <config-property name="userName" value=" "/>
    <config-property name="password" value=" "/>
    <config-property name="eisName" value=" "/>
    <config-property name="serverName" value=" "/>
    <config-property name="workspace" value=" "/>
    <config-property name="portNumber" value=" "/>
    <config-property name="persistentConnection" value=" "/>
    <config-property name="keepAlive" value=" "/>
    <config-property name="firewallProtocol" value=""/>
    <config-property name="connectTimeout" value=""/>
    <config-property name="encryptionProtocol" value=""/>
    <config-property name="encryptionKeyName" value=""/>
    <config-property name="encryptionKeyValue" value=""/>
  </connector-factory>
</oc4j-connector-factories>
```

The following table lists the properties that must be specified:

Property	Description
<code>location</code>	Specifies the JNDI location where Oracle Application Server should bind the connection factory instance for application components.
<code>eisName</code>	Sets the name of the adapter to use. The adapter is defined in the Oracle Connect server using Oracle Studio, as described in <a href="#">"Setting Up an Oracle Connect Adapter"</a> .
<code>serverName</code>	Sets the TCP/IP address or host name where the Oracle Connect daemon is running. The daemon runs on the computer specified at the beginning of <a href="#">"Setting Up the IBM OS/390 or z/OS Platform in Oracle Studio"</a> .  <b>See Also:</b> <a href="#">Appendix C, "Advanced Tuning of the Daemon"</a> for details about the daemon
<code>workspace</code>	Specifies the name of an Oracle Connect server workspace to use. The default workspace is Navigator.  <b>See Also:</b> <a href="#">"Workspaces"</a> on page C-7 for details about workspaces
<code>portNumber</code>	Specifies the TCP/IP port where the Oracle Connect daemon is running on the server. The default port is 2552.

Property	Description
userName (optional)	Specifies a user who can access the Oracle Connect server. The user is defined in the Oracle Connect daemon configuration.  <b>See Also:</b> <a href="#">"Daemon Security"</a> on page C-5 and <a href="#">"WS Security"</a> on page C-16 for details about users allowed to access an Oracle Connect server
password (optional)	Specifies a valid password for the user.
persistentConnection (optional)	Set to true or false. When set to true, connections can persist across multiple requests or connection context changes. It is recommended to set this property to true.
keepAlive (optional)	Set to true or false. When set to true, the socket used for the connection is always kept open. It is recommended to set this property to true.
firewallProtocol (optional)	Specifies the firewall protocol used: either none or fixedNat (the Nat protocol using a fixed address for the daemon). The default is none.
connectTimeout (optional)	Specifies the connection timeout in seconds. The default is 0, meaning that there is no connection timeout.
encryptionProtocol (optional)	Specifies the name of encryption protocol to use. The default is null. The RC4 protocol is supported.
encryptionKeyName (optional)	Specifies the name of the symmetric encryption key to use.
encryptionKeyValue (optional)	Specifies the value of the symmetric encryption key to use.

## Using the CCI API to Develop Applications

You can develop applications to run adapter interactions using the Common Client Interface (CCI) API.

Perform the following steps to use the CCI API with the J2CA 1.0 IMS/TM adapter:

1. Select a `ConnectionFactory` for the J2CA 1.0 IMS/TM adapter.
2. Create a `Connection` object using this `ConnectionFactory`. A `Connection` is a handle to the underlying network connection to the EIS, which is identified in the `oc4j-ra.xml` file by the `serverName` property.
3. Create a `Connection` object using this `ConnectionFactory`. Specify the interaction properties using an `AttuInteractionSpec` object. The `AttuInteractionSpec` object has the following format:

```
AttuInteractionSpec(java.lang.String name, int verb, int timeOut)
```

The following table describes the properties that can be specified:

Property	Description
name	Specifies the interaction name to be executed.

Property	Description
verb	Specifies the mode for the interaction: SYNC_SEND, SYNC_SEND_RECEIVE, or SYNC_RECEIVE.
timeOut	Specifies the time (in milliseconds) to wait for an EIS to run the specified interaction.

The following is an `InteractionSpec` sample:

```
AttuInteractionSpec iSpec = new AttuInteractionSpec("query",
    javax.resource.cci.InteractionSpec.SYNC_RECEIVE, 60);
javax.resource.cci.RecordFactory rf = new AttuRecordFactory(con,
    mcf.getLogger());
javax.resource.cci.MappedRecord queryRecord = rf.createMappedRecord("query"),
queryRecord.put("##text", "select * from disam:nation");
javax.resource.cci.Record oRec = interaction.execute(iSpec, queryRecord);
```

4. Invoke the `execute` method on the interaction to initiate a call to the EIS. Pass any data for the interaction as input and output records.
5. After the interactions have been processed, close the `Interaction` and `Connection` objects.

## Configuring Multiple Adapters

Each J2CA 1.0 IMS/TM adapter requires an entry in the `oc4j-ra.xml` file as described in ["Configuring the J2CA 1.0 IMS/TM Adapter"](#) on page 3-2.

**See Also:** *Oracle Application Server Adapter Concepts Guide*

## Updating Configuration Information

You can change configuration settings for a resource adapter by editing the relevant `connector-factory` entry in the `oc4j-ra.xml` file. For these changes to take effect, you need to stop and restart Oracle Application Server.

---

## Integrating OracleAS Adapter for IMS/TM with Oracle BPEL Process Manager

OracleAS Adapter for IMS/TM enables connectivity to Oracle BPEL Process Manager through the standard Web Services Description Language (WSDL) partner link mechanism.

Oracle BPEL PM enables users to capture IMS/TM native interactions as WSDL-based services. These services can be used from within the business process through an Invoke or Receive activity, which is associated with a partner link.

This chapter includes the following sections:

- [Integrating OracleAS Adapter for IMS/TM with Oracle BPEL Process Manager](#)
- [Using OracleAS Adapter for IMS/TM as Outbound Link](#)
- [Using OracleAS Adapter for IMS/TM as Inbound Link](#)
- [Updating Outbound and Inbound Interactions](#)

### Integrating OracleAS Adapter for IMS/TM with Oracle BPEL Process Manager

Oracle BPEL Process Manager provides a comprehensive and easy-to-use solution for creating, deploying and managing BPEL business processes. Oracle BPEL Process Manager is based on the Service Oriented Architecture (SOA) to provide enterprises with flexibility, interoperability, reusability, extensibility and rapid implementation of Web services and business processes. Oracle BPEL Process Manager reduces the overall costs of management, modification, extension and redeployment of existing business processes. Each business activity is a self-contained, self-describing, modular application whose interface is defined by the WSDL, and the business process is modeled as a Web Service.

A Web Service is first published and then composed or orchestrated into business flows. Publishing a service is implemented by taking a function within an existing application or system and making it available in a standard way, while orchestration is implemented by composing multiple services into an end-to-end business process. The interactions defined as part of the configuration of OracleAS Adapter for IMS/TM, are integrated into the orchestration as partner links.


**See Also:** *Oracle Application Server Adapter Concepts Guide*

## Using OracleAS Adapter for IMS/TM as Outbound Link

OracleAS Adapter for IMS/TM can be integrated with an Oracle BPEL Process Manager project to provide connectivity to IMS/TM data through Oracle Connect.


To use OracleAS Adapter for IMS/TM as an outbound link, perform the following steps:

1. Open the relevant Oracle BPEL Process Manager project in the BPEL Designer.
2. Select **Partner Link** from the component palette and drag the link to the Partner Links area in the project orchestration. The Create Partner Link screen is displayed.
3. Click **WSIL Browser**. The WSDL Chooser screen opens, displaying a list of the available connections.
4. Expand the node of the required connection, and select **Adapters**.
5. Expand the **Adapters** node and select **Legacy**.
6. Expand the **Legacy** node. The available servers are listed.
7. Expand the node of the required server. The available daemons for the selected server are listed.
8. Expand the node of the required daemon. The available workspaces for the selected daemon are listed.
9. Expand the node of the required workspace. The available adapters for the selected workspace are listed.
10. Expand the node of the required adapter and select the relevant interaction from the list, as shown in the following figure:



11. Click **OK**.

12. Specify the value in the list for the **Partner Role** field, as shown in the following figure:



13. Click **OK** to add the interaction to the orchestration as a partner link.  
The interaction is now included in the orchestration.

## Using OracleAS Adapter for IMS/TM as Inbound Link


OracleAS Adapter for CICS can be integrated with an Oracle BPEL Process Manager project to provide connectivity from CICS data through Oracle Connect.

To use OracleAS Adapter for IMS/TM as an inbound link, perform the following steps:


1. Open the relevant Oracle BPEL Process Manager project in the BPEL Designer.
2. Select **PartnerLink** from the component palette and drag the link to the Partner Links area in the project orchestration.  
The Create Partner Link screen is displayed.
3. Click **WSIL Browser**. The WSDL Chooser screen opens, displaying a list of the available connections.
4. Expand the node of the required connection, and select **Adapters**.
5. Expand the **Adapters** node and select **Legacy**.
6. Expand the **Legacy** node. The available servers are listed.
7. Expand the node of the required server. The available daemons for the selected server are listed.
8. Expand the node of the required daemon. The available workspaces for the selected daemon are listed.
9. Expand the node of the required workspace. The available adapters for the selected workspace are listed.



10. Expand the node of the required adapter and select the relevant interaction from the list, as shown in the following figure:



11. Click **OK**.
12. Specify the value in the **My Role** list as shown in the following figure:



13. Click **OK** to add the interaction to the orchestration as a partner link.
- The interaction is now included in the orchestration.

## Updating Outbound and Inbound Interactions

Oracle BPEL Process Manager samples the metadata, including the schemas, interactions, and their definitions from the repository, in real-time.

When you are modifying an adapter or its interaction definitions using Oracle Studio, you are required to refresh the server process in order for the changes to take effect, as described in ["Modeling Interactions for OracleAS Adapter for IMS/TM"](#) on page 2-18.



The changes made will be saved to the repository only when the server process is refreshed in Oracle Studio.

If you delete an existing interaction, Oracle BPEL Process Manager prompts with an error message, stating that the required interaction could not be invoked because it is not available. In this situation, you need to redeploy the business process in Oracle BPEL Process Manager.



---

## Troubleshooting OracleAS Adapter for IMS/TM

Troubleshooting Oracle AS Adapter for IMS/TM involves checking various definitions and properties in Oracle Connect, including daemon status, workspace options, server parameters, and various system logs.

This chapter contains the following sections:

- [Troubleshooting the Daemon](#)
- [Resolving Communication Errors](#)
- [Resolving Specific Errors](#)

### Troubleshooting the Daemon

Troubleshooting the daemon and the communication between Oracle Application Server and OracleAS Adapter for IMS/TM is performed using Oracle Studio. It is used to monitor the daemon and server activity and control what happens to the daemon and server processes.

**See Also:** [Appendix C, "Advanced Tuning of the Daemon"](#) for details about the configuration settings

This section contains the following topics:

- [Starting the Daemon](#)
- [Shutting Down the Daemon](#)
- [Monitoring the Daemon During Run Time](#)
- [Daemon Logs](#)

### Starting the Daemon

The daemon is started when OracleAS Adapter for IMS/TM is installed. In case you have shut down the daemon, as described in "[Shutting Down the Daemon](#)" on page 5-2, you can restart the daemon as described in the following task.

---

**Note:** The daemon is started on the IBM OS/390 or z/OS platform. It cannot be started remotely using Oracle Studio.

---

## Task: Starting the Daemon

Activate `INSTROOT.USERLIB(ATTDAEMN)` as a started task to invoke the daemon. For example, in the SDSF screen enter the following:

```
'/s ATTDAEMN'
```

Where `INSTROOT` is the high-level qualifier where Oracle Connect is installed.

**See Also:** ["Starting the Daemon"](#) on page 2-10 for details about the ATTDAEMN JCL

## Shutting Down the Daemon

To shut down the daemon, use Oracle Studio, as follows:

1. From the **Start** menu, select **Programs, Oracle**, and then select **Studio**.
2. Select the computer defined in ["Setting Up the IBM OS/390 or z/OS Platform in Oracle Studio"](#) on page 2-14.
3. Right-click the computer and select **Open Runtime Perspective**.
4. In the Runtime Explorer, right-click the computer, and select **Shutdown Daemon**.

## Monitoring the Daemon During Run Time

Use the Runtime Manager perspective of Oracle Studio to monitor the daemon during run time.

1. From the **Start** menu, select **Programs, Oracle**, and then select **Studio**.
2. Right-click the computer defined in ["Setting Up the IBM OS/390 or z/OS Platform in Oracle Studio"](#) on page 2-14 in the Configuration Explorer and select **Open Runtime Perspective**.

You can manage the daemon by expanding the relevant node, daemon, workspace or server process, and choosing the relevant option, as described in the following sections.

### Daemon (Computer) Options

Right-click the daemon to display the options available for it, including the ability to display the daemon log.

The following table lists the available options:

Option	Description
Status	Checks the status of the daemon. The information about the daemon includes the daemon name, configuration used, the active client sessions, and logging information.
Reload Configuration	Reloads the configuration after any changes. Any servers currently started are not affected by the changed configuration.  <b>See Also:</b> <a href="#">Appendix C, "Advanced Tuning of the Daemon"</a> for details about the configuration settings.

Option	Description
View Log	Displays the daemon log. For details see " <a href="#">Daemon Logs</a> " on page 5-4.
View Events	This option is for future use.
Daemon Properties	Displays information about the computer where the daemon is running, such as the physical address and any username and password needed to access the computer.
Shutdown Daemon	Shuts down the daemon on the computer.
Rename	Enables to change the name of the daemon displayed in the Runtime Explorer.
Remove	Removes the daemon from the Runtime Explorer.
Edit Daemon Configuration	Opens the daemon editor, enabling you to reconfigure the daemon.  <b>See Also:</b> <a href="#">Appendix C, "Advanced Tuning of the Daemon"</a> for details about the configuration settings.
Refresh	Refreshes the display.

## Workspace Options

Right-click a workspace to display the options available for the workspace, including the ability to display the workspace log.

The following table lists the available options:

Option	Description
Status	Checks the status of the workspace, whether it is available or not.
Reload Configuration	Reloads the configuration of the workspace after any changes. Any servers currently started are not affected by the changed configuration.
View Log	Displays the log for all servers for the workspace. For details see " <a href="#">Daemon Logs</a> " on page 5-4.
View Events	This option is for future use.
End Unused Servers	Ends all server processes for the workspace, that are not active. All available and unconnected servers are terminated and any connected servers are marked and terminated on release.  Use this option when changes to the daemon configuration were made after servers were started up. On the next operation, servers are restarted, based on the new settings.
End All Servers	Ends all the active server processes for the specified workspace, regardless of whether the server has an active client.

Option	Description
Edit Workspace Configuration	Opens the daemon editor to enable you to reconfigure the workspace.  <b>See Also:</b> <a href="#">Appendix C, "Advanced Tuning of the Daemon"</a> for details about the configuration settings.
Refresh	Refreshes the display.

### Server Options

Right-click a server to display the options available for the server, including the ability to display the server log.

The following table lists the available options:


Option	Description
Status	Checks the status of the server. The information about the server includes the server mode and the number of active client sessions for the server.
View Log	Displays the server log. For details see " <a href="#">Daemon Logs</a> " on page 5-4.
View Event	This option is for future use.
End	Ends the server process.
Refresh	Refreshes the display.

### Daemon Logs

Oracle Connect produces a number of logs that you can use to troubleshoot problems. The daemon manages the following logs:

- The daemon log
- The workspace log
- The server process log

The Runtime Manager perspective of Oracle Studio provides a monitor for these logs as shown in the following figure:



Display the required log by right-clicking the level you want (daemon, workspace or server) and selecting the **View Log** option. Each log is displayed in a different tab. You can flick between logs by clicking the required tab.

### The Daemon Log Monitor

The daemon log displays activity between clients and the daemon, including clients logging in and logging out from the daemon. You can change the level of logging by clicking **Properties**. The following levels of logging are available:

- none: The log displays who has logged in and out from the daemon.
- error: The log displays who has logged in and out from the daemon and any errors that have been generated.
- debug: The log displays who has logged in and out from the daemon, any errors that have been generated, and any tracing that has been specified in the daemon configuration.

**See Also:** ["Daemon Logging"](#) on page C-3 for details

### The Workspace Log Monitor

The workspace log displays information about the workspace being used by the client. You can change the level of logging by clicking **Properties**. The following levels of logging are available:

- none: The log displays who has connected and disconnected from the server process.
- error: The log displays who has connected and disconnected from the server process and any errors that have been generated.

- **debug:** The log displays who has connected and disconnected from the server process, any errors that have been generated, and any tracing that has been specified in the daemon configuration.

**See Also:** ["WS Logging"](#) on page C-14 for details

### The Server Log Monitor

The server log displays activity between clients and the server process used by that client to handle the client request. You can change the level of logging by clicking **Properties**. The following levels of logging are available:

- **none:** The log displays who has connected and disconnected from the server process.
- **error:** The log displays who has connected and disconnected from the server process and any errors that have been generated.
- **debug:** The log displays who has connected and disconnected from the server process, any errors that have been generated, and any tracing that has been specified in the daemon configuration.

**See Also:** ["WS Logging"](#) on page C-14 for details

## Resolving Communication Errors

When Oracle Studio disconnects from the IBM OS/390 or z/OS computer, the computer is displayed in Oracle Studio with an X in a red circle. If this situation occurs, try to access the computer later.

The following table describes the various scenarios that may exist when OracleAS disconnects from the IBM OS/390 or z/OS computer.

**Table 5–1 Scenarios When a Client Is Disconnected**

Scenario	Idle (Not Processing a Client Request)	Processing a Client Request
Explicit Disconnect (client explicitly closes connection or client program terminates)	The server is immediately notified of the disconnect and either becomes available for use by another client or terminates (if it is not reusable).	The server does not know that the client has disconnected and continues processing. When processing completes, the server tries to reply to the client and immediately gets an error that the connection was lost. The server either becomes available for use by another client or terminates (if it is not reusable).
Abrupt Disconnect (client closed without proper shutdown or client system hanged and communication disconnected)	The server does not know that the client has disconnected and remains in the idle state. After timing out based on whichever comes first of the value for the client idle timeout daemon workspace parameter or the TCP/IP KEEPALIVE parameter, the server is notified of the disconnect and either becomes available for use by another client or terminates (if it is not reusable).	The server does not know that the client has disconnected and continues processing. When processing completes, the server tries to reply to the client. After an interval (typically several minutes, depending on the TCP/IP configuration), during which the TCP/IP subsystem retries sending the message to the client, the server assumes that the client has terminated and notifies the server that the connection has been closed. The server either becomes available for use by another client or terminates (if it is not reusable).

To troubleshoot client/server communication problems, you need to be familiar with the following:

- Daemon configuration settings.



- Oracle Connect security.
- TCP/IP subsystem. OracleAS Adapter for IMS/TM uses TPC/IP for internal intermachine communications.
- System details, such as the account name and password of the administrator account, the IP address of the computers involved and whether a portmapper is being used.

## Resolving Specific Errors

The following error messages relate to errors received from Oracle Connect.

### **C007: Server initialization failed.**

**Cause:** The daemon failed to start its network service.

**Action:** Check the processes being run on the system to see whether another daemon or program is using the port specified in the `oc4j-ra.xml` file for the adapter.

**Action:** Check the TCP/IP subsystem on the current computer by trying to ping it or run FTP or Telnet to or from it.

**Action:** Check whether the daemon has privileges to use the TCP/IP services on the current computer with the port specified in the `oc4j-ra.xml` file for the adapter.

### **C008: Setting server event handler failed.**

**Cause:** Internal error.

**Action:** Contact Oracle Support Services.

### **C009: IRPCD process has been terminated by user request.**

**Cause:** This message is informational only. The daemon successfully shut down.

**Action:** No action required.

### **C00A: Application %s not found.**

**Cause:** The requested workspace does not exist.

**Action:** Check that the workspace defined in the `oc4j-ra.xml` file is also defined in the daemon configuration on the IBM OS/390 or z/OS platform. Use the Status option in the Runtime Manager perspective.

### **C00B: Invalid IRPCD client context.**

**Cause:** A non-Oracle Connect program is trying to connect to the daemon.

**Action:** Check the processes and kill the relevant process with a system command.

### **C00C: Daemon request requires a server login.**

**Cause:** A non-Oracle Connect server or program was trying to use a daemon service reserved for Oracle Connect servers.

**Action:** Check the processes and kill the relevant process with a system command.

### **C00D: Daemon request requires a client login.**

**Cause:** The requested daemon requires a valid client login, which was not supplied.

**Action:** Reissue the command and specify a username and password.

**Action:** Edit the user profile in Oracle Studio to specify a valid username and password for the IBM OS/390 or z/OS platform.

**See Also:** ["Setting Up Run-time User Access to the IBM OS/390 or z/OS Platform"](#) on page 2-17 for details

**C00E: Daemon request requires an administrator login.**

**Cause:** The requested daemon service requires an administrative login.

**Action:** Edit the daemon security in Oracle Studio to specify a valid administrator username and password.

**See Also:** ["Daemon Security"](#) on page C-5 for details

**C00F: Anonymous client logins are not allowed.**

**Cause:** The daemon is configured to require a valid username and password, which were not supplied.

**Action:** Enable anonymous client access in daemon security in Oracle Studio.

**See Also:** ["Daemon Security"](#) on page C-5 for detail

**Action:** Edit the user profile in Oracle Studio to specify a valid username and password for the IBM OS/390 or z/OS platform.

**See Also:** ["Setting Up Run-time User Access to the IBM OS/390 or z/OS Platform"](#) on page 2-17 for details

**C010: Anonymous server logins are not allowed.**

**Cause:** Internal error.

**Action:** Contact Oracle Support Services.

**C011: Client has already timed out.**

**Cause:** A server process was started on behalf of a client and the client has timed out before the server completed its startup.

**Action:** Increase the Connect timeout value for the server workspace in the WS Info. section of the daemon configuration.

**See Also:** ["WS Info."](#) on page C-8 for details

**C012: Invalid username/password.**

**Cause:** Invalid username/password supplied when logging on to the daemon.

**Action:** See the daemon log file for the reason that the username/password were not accepted.

**Action:** Edit the user profile in Oracle Studio to specify a valid username and password for the IBM OS/390 or z/OS platform.

**See Also:** ["Setting Up Run-time User Access to the IBM OS/390 or z/OS Platform"](#) on page 2-17 for details

**Action:** Make sure the daemon is started from an APF-authorized account that is allowed to check for system usernames and passwords.

**C014: Client connection limit reached - try later.**

**Cause:** The maximum number of server processes for the workspace has been reached, and none of the active servers could accept the client connection.

**Action:** Increase the value of the `Number of sub-tasks` in the `WS Server` section of the daemon configuration.

**See Also:** ["WS Server"](#) on page C-10 for details

**Action:** Try running the command later.

**C015: Failed to start server process.**

**Cause:** The Oracle Connect daemon failed to start a server process or the started server failed upon starting up.

**Action:** See the daemon and server logs for the reason the server did not start. For example, you might receive an message with a reason specified in the log file similar to the following: `[C015] Failed to start NAVIGATOR server process: No server account name defined for anonymous client; code: -1601: SQL code: 0`

**Action:** If you use impersonation, check the user profile on the client. Also see C069.

---

---

**To set impersonation:** APF authorize all the steplibs in the server script on OS/390 computer.

In the **WS Security** tab of the Navigator workspace under the daemon node in the **Configuration Explorer**, check the **Use specific workspace account** and clear the **Workspace account** field of all values.

---

---

**C016: Unexpected server state.**

**Cause:** Internal error.

**Action:** Contact Oracle Support Services.

**C017: Active daemon clients exist. Shutdown canceled.**

**Cause:** One or more clients are still connected to the daemon.

**Action:** Wait until all the clients log off the daemon and then retry the shutdown operation.

**C019: Request is not granted because someone else is locking it.**

**Cause:** A request to lock a resource managed by the daemon was denied because another user has locked the resource.

**Action:** Wait for the other user to release the resource.

**C01A: Lock %s not found.**

**Cause:** A request to free a resource was denied because the caller did not lock that resource (for example, another user shut down the daemon you are working with).

**Action:** Contact Oracle Support Services.

**C01B: Unexpected error in %s.**

**Cause:** Internal error.

**Action:** Contact Oracle Support Services.

**C01C: Cannot update configuration without \_APPLICATIONS lock.**

**Cause:** Internal error.

**Action:** Contact Oracle Support Services.

**C01D: Need to lock the application first.**

**Cause:** Internal error.

**Action:** Contact Oracle Support Services.

**C01F: Cannot set configuration of a deleted application.**

**Cause:** Internal error.

**Action:** Contact Oracle Support Services.

**C020: Failed in looking up host name (gethostname())**

**Cause:** Cannot connect to the remote computer.

**Action:** Check that the name specified for the computer in the `oc4j-ra.xml` file is correct.

**Action:** Check that a domain name server (DNS) is available to look up the host name.

**Action:** Check the TCP/IP subsystem on the computer by trying to ping it or run FTP or Telnet to or from it.

**C021: Required variable %s not found**

**Cause:** An environment variable required by the Oracle Connect server was not defined when the server started up.

**Action:** Check whether the startup script makes any changes to the environment variables used by Oracle Connect.

**Action:** Check whether the system-defined environment size is sufficiently large for Oracle Connect.

**C022: Server failed to connect and register with the daemon.**

**Cause:** An Oracle Connect server started by the daemon was not able to connect or register back with the daemon.

**Action:** Try to connect again.

**Action:** Increase the Connect timeout value for the server workspace in the WS Info. section of the daemon configuration.

**See Also:** ["WS Info."](#) on page C-8 for details

**Action:** Check that the startup script for the workspace launches the correct version of Oracle Connect.

**Action:** Increase the value of the `Set maximum number of servers` and/or `Maximum parameter for the Clients per server limit` in the WS Server section of the daemon configuration.

**See Also:** ["WS Server"](#) on page C-10 for details

**C023: Call made to unregistered module %d.**

**Cause:** Internal error.

**Action:** Contact Oracle Support Services.

**C024: Failed to create a socket.**

**Cause:** An error occurred within the TCP/IP subsystem.

**Action:** Check whether you have sufficient system privileges.

**Action:** Check the TCP/IP subsystem on the computer by trying to ping it or run FTP or Telnet to or from it.

**C025: Failed to set socket option %s**

**Cause:** An error occurred within the TCP/IP subsystem.

**Action:** Check whether you have sufficient system privileges.

**Action:** Check the TCP/IP subsystem on the computer by trying to ping it or run FTP or Telnet to or from it.

**C026: Failed to bind server to port %s**

**Cause:** An Oracle Connect server or daemon was not able to bind to the specified port.

**Action:** Check whether another program is holding the port that was specified in the `oc4j-ra.xml` file for the adapter.

**Action:** Check whether you have sufficient system privileges.

**C027: Cannot create TCP service for %s**

**Cause:** An error occurred within the TCP/IP subsystem

**Action:** Check the TCP/IP subsystem on the computer by trying to ping it or run FTP or Telnet to or from it.

**C028: Unable to register (%s, %d, tcp)**

**Cause:** This error may happen when a portmapper is used (*host:a*) but the portmapper is not available.

**Action:** Enable the portmapper.

**Action:** Avoid using the portmapper (by not using `:a` when starting the daemon).

**C029: Failed to create a server thread**

**Cause:** Internal error.

**Action:** Contact Oracle Support Services.

**C02A: Server thread failed to start**

**Cause:** Internal error.

**Action:** Contact Oracle Support Services.

**C02B: Stopping the %s server - no client**

**Cause:** A server that was started by the Oracle Connect daemon to service a client did not get a client connection request within one minute. The server terminates.

**Action:** In most cases, the client was terminated by a user request, so no specific action is required.

**Action:** If no client can connect to the server, it may be that the server has multiple network cards and the Oracle Connect daemon is not aware of this. In this case, start the daemon with an IP address.

**C02C: Unexpected event - a termination signal intercepted**

**Cause:** Internal error.

**Action:** Contact Oracle Support Services.

**C02D: Modified transport, context unknown/lost**

**Cause:** Internal error.

**Action:** Contact Oracle Support Services.

**C02F: Corrupted arguments passed to procedure**

**Cause:** Internal error.

**Action:** Contact Oracle Support Services.

**C030: Unable to free arguments for %s() of %s**

**Cause:** Internal error.

**Action:** Contact Oracle Support Services.

**C031: Cannot register a non-module RPC %s**

**Cause:** Internal error.

**Action:** Contact Oracle Support Services.

**C032: An IRPCD program is required**

**Cause:** Internal error.

**Action:** Contact Oracle Support Services.

**C033: An IRPCD super-server is required for module events**

**Cause:** Internal error.

**Action:** Contact Oracle Support Services.

**C034: An invalid super-server module ID was specified, %d**

**Cause:** Internal error.

**Action:** Contact Oracle Support Services.

**C035: Out of memory**

**Cause:** Not enough memory to service a client request.

**Action:** Increase process memory quota or add memory to the system.

**C036: Failed to register RPC procedure module %s**

**Cause:** Internal error.

**Action:** Contact Oracle Support Services.

**C037: Failed to register an invalid RPC procedure number %x**

**Cause:** Internal error.

**Action:** Contact Oracle Support Services.

**C038: Cannot re-register RPC procedure number %x**

**Cause:** Internal error.

**Action:** Contact Oracle Support Services.

**C042: Remote call to %s failed; %s**

**Cause:** Remote call to API failed.

**Action:** Check the daemon log file.

**Action:** If necessary, change the level of detail written to the log file to help resolve the problem.

**See Also:** ["Daemon Logging"](#) on page C-3 for details

**C043: Failed to connect to host %s;%s**

**Cause:** The remote host is not correctly defined to Oracle Connect or is not working.

**Action:** Check the remote computer definition in the `oc4j-ra.xml` file for the adapter.

**Action:** Check that the daemon is up on the IBM OS/390 or z/OS platform. Use the Status option in the Runtime Manager perspective.

**Action:** Check the network connection by trying to ping the host computer or run FTP or Telnet to or from it.

**C045: Failed to create a service thread**

**Cause:** The server failed to create a thread to service a client request.

**Action:** A system or process quota limit has been exceeded. Either increase the quota or lower the **Clients per server limit** field value in the WS Info. section of the daemon configuration.

**See Also:** ["WS Info."](#) on page C-8 for details

**C047: %s out of memory**

**Cause:** Not enough memory was available to Oracle Connect to complete a requested operation.

**Action:** Terminate unnecessary processes running on the server.

**Action:** Add more memory to the system.

**Action:** Allow the process to use more memory.

**Action:** Limit the number of processes the daemon may start. If the demand for servers exceeds the number of available servers, clients get a message telling them the maximum number of servers has been reached and asking them to try again later.

**C066: Communication error with the server%s**

**Cause:** Connection to the Oracle Connect daemon or server failed, or an established session with a server has failed.

**Action:** Check the remote computer definition in the `oc4j-ra.xml` file.

**Action:** Check that the daemon is up on the IBM OS/390 or z/OS platform. Use the Status option in the Runtime Manager perspective.

**Action:** In case of a network problem, check the network connection by trying to ping the host computer or run FTP or Telnet to or from it.

**C067: Unexpected error occurred in server function %s**

**Cause:** One of the server functions has exited with an exception, such as an Abend, or Invalid Instruction.

**Action:** Contact Oracle Support Services.

**C068: Fail to login daemon**

**Cause:** The daemon is not running on the server computer.

**Action:** Use the Status in Oracle Studio Runtime Manager perspective to check whether a daemon is running on the server

**Action:** Have the system administrator reinstall Oracle Connect on the server.

**C069: Fail to get server**

**Cause:** The Oracle Connect daemon on the server computer could not start a server process to serve the client. A separate message provides more detail on why the server process could not start.

**Action:** There are many possible causes of this error. If the cause is not clear from the related message, see the Oracle Connect daemon log file on the server

**Action:** The resolution to this error is highly dependent on the particular cause. The following are some typical causes and resolutions.

**Action:** Some process creation quota was exceeded. Either try again later or increase the quota or the other relevant system resources.

**Action:** The server startup script failed.

**Action:** The username given is not allowed to use the requested server. Use an authorized username.

**Action:** A limit on concurrent clients for a server has been reached. Try again later.

**Action:** If you use impersonation, then check the user profile on the client. Also see C015.

**C06A: Failed to connect to server**

**Cause:** The server assigned to the client did not accept the client connection. A separate message provides more detail about why the server process did not accept the connection.

**Action:** See the daemon and server log files for the reason that the server was not available to accept its assigned client.

**C06B: Disconnecting from server**

**Cause:** A network failure, server failure or server program failure caused the connection to stop. The currently active transaction is stopped as well.

**Action:** Oracle Connect automatically tries to reestablish a connection with a server upon the next SQL command issued against the server. Once the network or computer failure is corrected, the connection to the daemon is reestablished automatically.

**C070: Server failed to send reply to the client**

**Cause:** Server terminated unexpectedly.



**Action:** Unless the client was intentionally stopped (for example, using Control-C), contact Oracle Support Services.

**C071: Connection to server %s was disconnected. Cursors state was lost.**

**Cause:** Either a network failure, server failure, or a server program failure caused the connection to stop. The currently active transaction is stopped as well.

**Action:** Normally, Oracle Connect automatically tries to create a new session with the server upon the next attempt to access the server. If the network and server are accessible, the next operation should succeed. Otherwise, the network or server should be fixed before connection can be resumed.

**Action:** In case of a server crash not related to callable user code, contact Oracle Support Services.

**C072: Reconnect to server %s**

**Cause:** This is an informational message only. The client has reestablished its connection with the server.

**Action:** No action is required.

**C073: The parameters passed to the admin server are invalid: %s**

**Cause:** Internal error.

**Action:** Contact Oracle Support Services.

**C074: No authorization to perform the requested operation (%s)**

**Cause:** User/account has insufficient privileges.

**Action:** Grant administrative privileges to the user/account using the Administrator parameter of the Daemon Security or WS Security sections in the daemon configuration.

**See Also:** ["Daemon Security"](#) on page C-5 or ["WS Security"](#) on page C-16 for details

**C075: Failed to register daemon in the TCP/IP service table**

**Cause:** Registration of the daemon in the TCP/IP services file has failed.

**Action:** Check that the account running the daemon has the permissions to update the TCP/IP services file.

**E001: Failed in lock/release operation**

**Cause:** A lock or release operation of a global resource has failed. A separate message provides more details. The separate message specifies the cause of this error.

**Action:** There are various causes for this error, including lack of sufficient privileges or a system resource shortage.

**J0006: Operation on already closed connection was requested**

**Cause:** A request using a connection that was closed was attempted.

**Action:** Reopen the connection and try again.

**J0028: Internal Error: Unknown XML tag %s**

**Cause:** Internal error.

**Action:** Contact Oracle Support Services.

**J0030: Internal Error: Method %s needs to be overwritten**

**Cause:** Internal error.

**Action:** Contact Oracle Support Services.

**J0031: Internal Error: Required attribute %s not found in %s verb**

**Cause:** Internal error.

**Action:** Contact Oracle Support Services.

**J0032: Internal Error: %s ACP object was returned instead of %s as expected**

**Cause:** Internal error.

**Action:** Contact Oracle Support Services.

**J0033: Internal Error: Attempt to work with closed socket**

**Cause:** Internal error.

**Action:** Contact Oracle Support Services.

**J0034: Internal Error: corrupted message; %s bytes read instead of %s as expected**

**Cause:** XML sent from the client to the server has become corrupted.

**Action:** Check compression settings for XML transferred from the client to the server. If the setting are correct, retry sending the request from the client to the server.

**J0035: Internal Error: Invalid redirection address %s returned by daemon**

**Cause:** Internal error.

**Action:** Contact Oracle Support Services.

**J0036: %s: %s**

**Cause:** One of the following errors was received from the server: 0 - server.internalError, 1 - client.xmlError, 2 - client.requestError, 3 - client.noActiveConnection, 4 - server.resourceLimit, 5 - server.redirect, 6 - client.noSuchResource, 7 - client.authenticationError, 8 - client.noSuchInteraction, 9 - client.noSuchConnection, 10 - server.notImplemented, 11 - server.xaProtocolError, 12 - server.xaUnknownXID, 13 - server.xaDuplicateXID, 14 - server.xaInvalidArgument, 15 - client.autogenRejected, 16 - server.xaTransactionTooFresh, 17 - server.resourceNotAvailable, 18 - client.authorizationError, 19 - server.configurationError

**Action:** Review the server log file to determine the problem.

**J0037: Internal Error: No ACP response when %s was expected**

**Cause:** Internal error.

**Action:** Contact Oracle Support Services.

**J0039: Internal Error: ACP root is not found in the XML**

**Cause:** Internal error.

**Action:** Contact Oracle Support Services.

**J0040: Internal Error: Input record is required for interaction %s execution**

**Cause:** Internal error.

**Action:** Contact Oracle Support Services.

**J0048: Invalid metadata type %s is passed to %s function**

**Cause:** A request for metadata was not fulfilled.

**Action:** Check the validity of the request.

**J0050: Key of the put method must be of type string**

**Cause:** In either a GET or PUT operation, the key must be a string.

**Action:** Change the key used in the operation to a valid key.

**J0059: Value %s is invalid for attribute %s**

**Cause:** A request for metadata was not fulfilled.

**Action:** Check the validity of the request.

**J0068: Value must be of type string**

**Cause:** In a PUT operation, the value must be a string.

**Action:** Change the value used in the operation to a valid value.

**J0069: Value must be of type MappedRecord**

**Cause:** In a PUT operation, the value must be a mapped record.

**Action:** Change the value used in the operation to a valid value.

**J0070: Value must be of type MappedRecord[]**

**Cause:** In a PUT operation, the value must be mapped record array.

**Action:** Change the value used in the operation to a valid value.

**J0071: Bad key for mapped record, #element or #element[] is required**

**Cause:** In a PUT operation, the value must be mapped record array.

**Action:** Change the key used in the record to a valid key.

**J0072: Value must be of type Object[]**

**Cause:** In a PUT operation, the value must be mapped record array.

**Action:** Change the value used in the operation to a valid value.

**J0078: In nonpersistent connection and non keep alive encryption is not supported - ignored**

**Cause:** Encryption is not supported for nonpersistent connections.

**Action:** There is no action to take. This warning can be ignored.

**J0079: Invalid argument passed to %s - Argument: %s, Value: %s**

**Cause:** The value pass.

**Action:** Change the argument used to a number.



---

## Advanced Features of OracleAS Adapter for IMS/TM

Oracle Connect includes a number of tuning parameters that can improve performance. Specifically, the daemon can be configured to optimize communication between the IBM OS/390 or z/OS platform and a client. In addition, the binding environment can be tuned to optimize request handling.

This chapter contains the following sections:

- [Configuring the Daemon for High Availability](#)
- [Configuring a Binding Environment](#)
- [Migration Considerations](#)
- [Security Considerations](#)
- [Transaction Support](#)

### Configuring the Daemon for High Availability

The daemon workspace is responsible for allocating server processes to clients. You can configure a workspace to use a pool of server processes so that a server process is always available for a client request. Use Oracle Studio to maintain daemon and daemon workspace parameters to control the allocation of server processes and their management in a pool.

You can also have a number of daemon workspace configurations. Therefore, you can create individual workspaces for use with different adapters.

### Adding a New Daemon Workspace Configuration

Use Oracle Studio to add a new daemon configuration. You can set up different daemon configurations for different situations.

Perform the following steps to add a new daemon workspace configuration:

1. From the **Start** menu, select **Programs, Oracle**, and then select **Studio**.
2. In the Configuration Explorer, expand the computer defined in "[Setting Up the IBM OS/390 or z/OS Platform in Oracle Studio](#)" on page 2-14.
3. Expand the **Daemons** node. The available daemon configurations are listed.
4. Right-click **IRPCD** and select **New Workspace**. The New Daemon Workspace screen is displayed.
5. Specify a name for the new workspace and optionally provide a description.

6. Specify whether you want default settings or copy the properties of an existing workspace.  
To copy the properties of an existing workspace, click **Ellipsis** and select the workspace from which you want to copy the properties.
7. Click **Next**. The Select Scenario screen is displayed.
8. Select the **Application Server using connection pooling** and click **Next**.
9. Continue through the wizard and specify the required values for the workspace.
10. To complete the workspace definition, click **Finish**.

The workspace is displayed under the **IRPCD** daemon node.

## Editing the Workspace

You edit a workspace by using the tabs described in the following table:

Tab	Description
WS Info	Specifies general information including the server type, the command procedure used to start the workspace, the binding configuration associated with this workspace and the timeout parameters.
WS Server Mode	Specifies workspace server information including features that control the operation of the servers started up by the workspace and allocated to clients.
WS Logging	Specifies parameters for logging and the format to use for a log file.
WS Security	Specifies administration privileges, user access, ports available to access the workspace and workspace account specifications.
WS Governing	This tab is not applicable for use with OracleAS Adapter for IMS/TM.

To access these tabs, perform the following steps using Oracle Studio:

1. From the **Start** menu, select **Programs, Oracle**, and then select **Studio**.
2. In the Configuration Explorer, expand the the computer defined in ["Setting Up the IBM OS/390 or z/OS Platform in Oracle Studio"](#) on page 2-14.
3. Expand the **Daemons** node. The daemon configurations available on this computer are listed.
4. Expand the **IRPCD** node. The daemon workspaces are listed.
5. Right-click **IRPCD** and select **Edit Workspace**.
6. Click the required tab, which contains the information you want to edit. For full details of the tabs and the fields in these tabs, refer to ["Workspaces"](#).
7. After editing the workspace, click **Save**.

## Configuring the Server Mode


The server mode determines how the daemon starts up new processes. The daemon supports the following server modes:

- **singleClient:** Each client receives a dedicated server process. The account in which a server process runs is determined either by the client login information or by the specific server workspace.

This mode enables servers to run under a particular user account and isolates clients from each other (because each receives its own process). However, this server mode incurs a high overhead due to process startup times and may use a lot of server resources (because it requires as many server processes as concurrent clients). The number of clients that share a process is determined by the Clients per server limit (the maximum number of concurrent clients a server process for the current workspace accepts).

- **reusable:** This is an extension of the single client mode. Once the client processing finishes, the server process does not die and can be used by another client, reducing startup times and application startup overhead. This mode does not have the high overhead of single client mode because the servers are already initialized. However, this server mode may use a lot of server resources (because it requires as many server processes as concurrent clients).
- The other modes can be set so that the server processes are reusable by setting the number of times a process can be reused with the Reuse limit value (the maximum number of times a particular server process can be reused or how many clients it can serve before it is retired). Reuse of servers enhances performance because it eliminates the need to repeat initializations. However, reuse runs a risk of higher memory leakage over time. The default for the Reuse limit field value is *None*, indicating that no reuse limit is enforced.

Set the server mode in the WS Server tab of the daemon workspace editor as shown in the following figure:



When using any of the server modes you can specify a pool of server processes. These server processes are started when the daemon starts and are maintained in a pool. The server processes are available for use by new client requests from the pool, saving initialization time.

Instead of starting a new server process each time one is requested by a client, the client receives a process immediately from the pool of available processes. When the client finishes processing, this server process either dies, or if reusable servers have been specified, it is returned to the pool.

You set up a pool of server processes by specifying the following parameters in the WS Server tab.

- **Initial number of servers:** The number of server processes that are prestarted for this workspace when the daemon starts up. These are available for use by new client processes with minimal initialization time. Instead of starting a new server process each time one is requested by a client, the daemon immediately allocates (to the client) a server from a pool of available servers. When the number of available server processes drops lower than the value specified in the Minimum number of available servers field, the daemon again starts server processes until the specified number of available servers is reached. The default for this parameter is 0, meaning that no servers are prestarted for this workspace.
- **Minimum number of available servers:** The minimum number of server processes in the prestarted server's pool before the Oracle Connect daemon resumes creating new server processes (up to the number specified in the Initial number of servers field value, described earlier). If this parameter is set to a value greater than that of the Initial number of servers field value, the daemon considers the value to be the same as the value specified in the Initial number of servers field. In this case, a new server process is started and added to the pool each time a server process is removed from the pool and allocated to a client). The default for this parameter is 0, meaning that new servers are created only when there are no other available servers.
- **Set maximum number of servers:** The maximum number of available server processes pooled for this workspace. If the server is reusable, once a client disconnects from the server, the daemon returns the server to the pool of available servers. If the limit is reached, excess server processes are discarded.
- **Number of sub-tasks:** The number of sub-tasks for a server that are prestarted for this workspace when the daemon starts up. In addition to setting up a pool of server processes as described earlier, you can set additional server processes as sub-tasks by specifying this parameter. Thus, setting 10 servers and 10 prestarted sub-tasks results in 100 tasks started (10 sub-tasks for each process).

## Configuring a Binding Environment

Each binding configuration includes the following:

- Environment settings, which are used to configure the environment used by any of the adapters defined in the binding
- Application adapters on the current computer


Configuring data sources and adapters is described in [Chapter 2, "Installing and Configuring OracleAS Adapter for IMS/TM"](#).

To configure environmental settings in Oracle Studio:

1. From the **Start** menu, select **Programs, Oracle**, and then select **Studio**.
2. In the Configuration Explorer, expand the node of the computer defined in ["Setting Up the IBM OS/390 or z/OS Platform in Oracle Studio"](#) on page 2-14.
3. Expand the **Bindings** node. The available binding configurations are listed.
4. Right-click **NAV** and select **Edit Binding**.
5. In the Properties tab edit the required environment settings as needed. To edit an environment setting, click the property category node, and then click the required value to edit.



The binding Properties tab is shown in the following figure:



The binding environment is divided into the following categories:

- [comm Category](#)
- [debug Category](#)
- [miscellaneous Category](#)
- [odbc Category](#)
- [oledb Category](#)
- [optimizer Category](#)
- [queryProcessor Category](#)
- [transactions Category](#)
- [tuning Category](#)

## comm Category

The following table lists the parameters that define the communication buffers:

Parameter	Description
comCacheBufferSize	Specifies the size of a memory buffer on a client, which is used by the Oracle Connect client/server to store read-ahead data. The default is 200000 bytes.
comMaxSocketSize	Specifies the maximum bytes that can be written in one chunk on a socket. The default is -1 (no limitation).
comMaxXmlInMemory	Specifies the maximum size of an XML document held in memory. The default is 65535 bytes.

Parameter	Description
comMaxXmlSize	Specifies the maximum size of an XML document passed to another computer. The default is 65535 bytes.

## debug Category

The following table lists the parameters that define debugging and logging operations.

Parameter	Description
acxTrace	When set to true, the input xml sent to the back-end adapter and the output xml returned by the back-end adapter, are written to the log.
analyzerQueryPlan	This parameter is not applicable for use with OracleAS Adapter for IMS/TM.
gdbTrace	This parameter is not applicable for use with OracleAS Adapter for IMS/TM.
generalTrace	When set to true, logs general trace information. The default writes only error messages to the log.
logFile	The high-level qualifier of the log file for messages. The following types of message are written to the log: <ul style="list-style-type: none"> <li>■ Error messages.</li> <li>■ Trace information and information about the query optimization strategy if generalTrace is set to true.</li> </ul>
oledbTrace	This parameter is not applicable for use with OracleAS Adapter for IMS/TM.
optimizerTrace	This parameter is not applicable for use with OracleAS Adapter for IMS/TM.
queryWarnings	This parameter is not applicable for use with OracleAS Adapter for IMS/TM.
traceDir	This parameter is not applicable for use with OracleAS Adapter for IMS/TM.

## miscellaneous Category

The following parameters define miscellaneous operations, including globalization support and the directory where temporary files are written.

Parameter	Description
codepage	For use with globalization support to identify the codepage for the workspace. See also: <a href="#">Appendix D, "Globalization Settings"</a> .

Parameter	Description
cvtSeverityLevel	<p>The data type conversion policy when a conversion error occurs:</p> <ul style="list-style-type: none"> <li>0 (Default): The data in the output column will be a null or empty value.</li> <li>1: The data in the output column will be a null or empty value and the error is reported to the log.</li> <li>2: An error is reported and processing stops</li> </ul>
edit	This parameter is not applicable for use with OracleAS Adapter for IMS/TM.
language	Identifies the application language. A default codepage is selected based on the value specified for this parameter. See also: <a href="#">Appendix D, "Globalization Settings"</a> .
nlsString	<p>Specifies the codepage used by a field whose data type is defined as "nlsString". Use this for a field whose codepage is other than that of the computer codepage. This parameter includes the following values:</p> <ul style="list-style-type: none"> <li>The name of the codepage.</li> <li>Whether the character set reads from right to left (as in middle eastern character sets). The default is false.</li> </ul>
tempDir	The directory where temporary files are written, including the temporary files created for use by hash joins and for sorting files. The default is the current high-level qualifier.

Parameter	Description
year2000Policy	<p>Determines the way 2-digit years are converted into 4-digit years. When the parameter year2000Policy is not set, or when it is set to a value outside the range of values defined for the policy, as described in the following paragraphs, a default value of 5 and the Sliding Base Year policy is used. Two policies are provided:</p> <ul style="list-style-type: none"><li>■ Fixed Base Year: year2000Policy is set to a value greater than, or equal to 1900. In this case, the value of year2000Policy is the first 4-digit year after 1900 that can be represented by a 2-digit year. For example, if year2000Policy is set to 1905, the years 2000-&gt;2004 will be represented by 00-&gt;04. All other 2 digits will map to 19xx.  This solution is most required if there is live data at the low end (close to the year 1900), which the user wants to keep with the current 2-digit format.  The user will probably change the base date only after ensuring that these old dates have been deleted from the data source.</li><li>■ Sliding Base Year: year2000Policy is set to a positive value less than 100. In this case, the value of year2000Policy represents the number of years ahead of the current year that can be represented by a 2-digit number. With each passing year the earliest year that can be represented by a 2-digit number changes to a year later.</li></ul>

### odbc Category

The odbc parameters are not applicable for use with OracleAS Adapter for IMS/TM.

### oledb Category

The oledb parameters are not applicable for use with OracleAS Adapter for IMS/TM.

### optimizer Category

The optimizer parameters are not applicable for use with OracleAS Adapter for IMS/TM.

### queryProcessor Category

The queryProcessor parameters are not applicable for use with OracleAS Adapter for IMS/TM.

## transactions Category

The following table lists the parameters that define the transaction support:

Parameter	Description
<code>convertAllToDistributed</code>	When set to <i>true</i> , converts all simple transactions into distributed transactions.
<code>convertAllToSimple</code>	When set to <i>true</i> , converts all distributed transactions into simple transactions.
<code>disable2PC</code>	When set to <i>true</i> , disables two phase commit capabilities, even in drivers that support two phase commit.
<code>logFile</code>	The high-level qualifier and name of the log file that logs activity when using transactions. The logfile parameter can also include the keyword NORRS after a comma (so that the format is log,NORRS) when RRS is not running on the OS/390 or z/OS platform.
<code>recoveryDelay</code>	The number of minutes from the start of a transaction before any recovery operation on that transaction can be attempted. The default is 15 minutes.
<code>useCommitConfirmTable</code>	This parameter is not applicable for use with OracleAS Adapter for IMS/TM.

## tuning Category

The tuning parameters are not applicable for use with OracleAS Adapter for IMS/TM.

## Migration Considerations

You can migrate an adapter configuration from one platform to another. The configuration information is stored in the Oracle Connect repository on the source platform and is exported to an XML file which can then be imported to the target platform. Note that when migrating a configuration, any file names and paths that are specific to the source platform must be changed to valid files on the target platform. Perform the following steps to migrate an adapter configuration using Oracle Studio.

1. From the **Start** menu, select **Programs, Oracle**, and then select **Studio**.
2. In the Configuration Explorer, right-click the computer defined in "[Setting Up the IBM OS/390 or z/OS Platform in Oracle Studio](#)" on page 2-14 and select **Export XML definitions**.
3. Specify the path and name of the XML file, which stores the XML representation and complete configuration.
4. Edit any paths in the XML definition to the paths required on the target platform. For example, the setting for the `serverLogFile` might need changing, depending on the platform.
5. Set up the target platform in Oracle Studio in the same way you set up the source platform, as described in "[Setting Up the IBM OS/390 or z/OS Platform in Oracle Studio](#)" on page 2-14.

6. In the Configuration Explorer, right-click the target computer and select **Import XML definitions**.
7. Import the XML file to the target platform.

## Security Considerations

Oracle Connect works within the confines of the platform security system. For example, on an OS/390 computer with RACF installed, and with the workspace server mode set to multi-tasking, a RACROUTE VERIFY is performed for each task in the address space, according to the client connection.

In addition, Oracle Connect provides the following security:

- Design Time: Security within Oracle Studio to grant access to Oracle Studio itself and to grant access to computers, user profiles and workspaces.
- Run time: Security used to access IMS/TM, including controlling the daemon for the access.

### Setting Design Time Security

Setting design time security is described in the following sections:

- Securing access to Oracle Studio is described in "[Setting Password Access to Oracle Studio](#)" on page 2-15.
- Securing rights to configure a computer in Oracle Studio is described in "[Specifying Users with Administrative Rights](#)" on page 2-16.
- Securing access to user profiles is accomplished by right-clicking the relevant user profile in Oracle Studio and selecting **Change Master Password**. In the dialog box that is displayed, specify a password that must be provided in the future to edit the specific user profile.
- Securing access to workspaces is accomplished by right-clicking the relevant workspace in Oracle Studio and selecting **Set Authorization**. In the dialog box that is displayed, specify a valid user and password that must be provided in the future to edit the specific workspace.

### Setting Run-time Security

During run time, security considerations are implemented as follows:

- When the client request accesses the legacy platform through the daemon, either anonymous access is allowed or a valid user name and password must be provided for the computer in the user profile. The userName and password properties in the J2CA 1.0 IMS/TM adapter are used at this stage to access the daemon.

---

---

**Note:** The user name used to access the daemon must also be the name of a user profile used.

---

---

- Access by the client must be through a valid port, according to the list of ports specified in the Workspace Access section of the WS Security tab in Oracle Studio. For details of the WS Security tab, refer to "[WS Security](#)" on page C-16.

---

**Note:** Access to the legacy platform through a firewall using the NAT protocol is specified when the computer is added to Oracle Studio.

---

- To be allocated a server process, the client must be granted anonymous access to the workspace or be listed in the Workspace Users section of the WS Security tab in Oracle Studio. For details of the WS Security tab, refer to ["WS Security"](#) on page C-16.
- The ability to run commands on the daemon, such as starting or stopping a daemon or ending server processes is available only to administrators who have been registered in Oracle Connect as a daemon administrator. A client is registered as a valid daemon administrator in the Daemon Security tab in Oracle Studio, as described in ["Daemon Security"](#) on page C-5.

---

**Note:** You can also specify administrators who can run commands only at the level of the workspace. Specify these administrators in the WS Security tab, as described in ["WS Security"](#) on page C-16.

---

## Transaction Support


OracleAS Adapter for IMS/TM supports two-phase commit and can fully participate in a distributed transaction.

---

**Note:** To use OracleAS Adapter for IMS/TM with 2PC, you must have RRS installed and configured.

---

To work with 2PC, set the `convertAllToDistributed` transaction environment property to true, as shown in the following figure:



To use two-phase commit capability to access data on the OS/390 or z/OS computer, define every library in the ATTSRVR JCL as an APF-authorized library.

To define a DSN as APF-authorized, in the SDSF screen enter the command:

```
"/setprog apf,add,dsn=instroot.library,volume=ac002"
```

Where *ac002* is the volume where you installed Oracle Connect and *INSTROOT* is the high level qualifier where Oracle Connect is installed.

If the Oracle Connect installation volume is managed by SMS, then when defining APF-authorization, enter the following command in the SDSF screen:

```
"/setprog apf,add,dsn=instroot.library,SMS"
```

Ensure that the library is APF-authorized, even after an IPL (restart) of the computer.

If RRS is not running, then OracleAS Adapter for IMS/TM can participate in a distributed transaction, as the only one-phase commit resource, only if the `logFile` transaction environment property includes the keyword `NORRS`, as shown in the following figure:

Property	Value
<input checked="" type="checkbox"/> comm	
<input checked="" type="checkbox"/> debug	
<input checked="" type="checkbox"/> misc	
<input checked="" type="checkbox"/> odbc	
<input checked="" type="checkbox"/> oledb	
<input checked="" type="checkbox"/> optimizer	
<input checked="" type="checkbox"/> queryProcessor	
<input checked="" type="checkbox"/> tempFeatures	
<input checked="" type="checkbox"/> transactions	
commitOnDestroy	false
convertAllToDistributed	true
convertAllToSimple	false
disable2PC	false
extendedLogging	false
logFile	logfile,NORRS
oleThreads	
recoveryDelay	
timeLimit	
useCommitConfirmTable	false
<input checked="" type="checkbox"/> tuning	

---

**Note:** If a log file is not specified, then the format for the `logFile` parameter when RRS is not running is: `,NORRS`.

---



---

## Advanced Tuning of the Metadata

Oracle Studio enables you to define adapter interactions, such as Outbound and Inbound interactions. In addition, Oracle Studio defines input and output structures used for these interactions. The interactions and input and output structures are maintained as metadata in the Metadata tab of Oracle Studio.

This appendix contains the following section:

- [Metadata for the Back-end Adapter](#)

### Metadata for the Back-end Adapter

Using Oracle Studio, perform the following steps to maintain the metadata for OracleAS Adapter for IMS/TM.

1. From the **Start** menu, select **Programs, Oracle**, and then select **Studio**.
2. Select the computer defined in "[Setting Up the IBM OS/390 or z/OS Platform in Oracle Studio](#)" on page 2-14.
3. Expand the **Bindings** node.
4. Expand the **NAV** binding node.
5. Expand the **Adapters** node to display the adapters.
6. Right-click the IMS/TM adapter in the Configuration Explorer and select **Edit Metadata** to open the Metadata tab.
7. Right-click the interaction in the Metadata Explorer and select **Edit**.

The metadata editor opens, displaying the General tab, with general table details. The following tabs are used to view and edit the metadata:

- [General Tab](#)
- [Interaction Tab](#)
- [Schema General Tab](#)
- [Schema Record Tab](#)
- [Source Tab](#)

### General Tab

Use the General tab to maintain information describing the adapter and the connection to the adapter.

The General tab is shown in the following figure:

The screenshot shows the 'General' tab of a configuration window. It includes sections for 'Details' (Name: Legacy, Description:), 'Connection' (Authentication mechanism: dropdown, Max Request size: text box, Max active connections: text box, Max idle timeout: text box), and 'Adapter specifications' (a table with Property and Value columns). The bottom of the window shows a tabbed interface with 'General' selected.

The General tab comprises fields, as listed in the following table:

Field	Description
Adapter definition name	Specifies the name of the adapter definition.
Description	Specifies an identifying description of the adapter.
Authentication mechanism	Specifies the authentication method used to access the adapter. The available mechanisms are: <ul style="list-style-type: none"> <li>■ kerbv5</li> <li>■ none</li> <li>■ basic password</li> </ul>
Max request size	Specifies the maximum size in bytes for an XML request or reply. Larger messages are rejected with an error.
Max active connections	Specifies the maximum number of simultaneous connections for an adapter (per process).
Max idle timeout	Specifies the maximum time, in seconds, that an active connection can stay idle. After that time, the connection is closed.
Adapter Specifications	Specifies the adapter-specific properties for an interaction. The IMS/TM back-end adapter does not have any adapter-specific properties.

## Interaction Tab

Use the Interaction tab to define the general details of the interaction in addition to its input and output definitions.

The Interactions tab is displayed in the following figure:

Details

Name:

Description:

Mode:

Input/Output definitions

Input record:

Output record:

Interaction specific parameters

Property	Value
transaction	getOrd

General | Interaction | Schema General | Schema Record | Source

The Interaction tab comprises fields, as listed in the following table:

Field	Description
Interaction name	Specifies the name of the interaction.
Description	Provides a descriptive identifier for the interaction.
Mode	<p>Determines the interaction mode. The following interaction modes are available:</p> <ul style="list-style-type: none"> <li>■ sync-send-receive: The interaction sends a request and expects to receive a response.</li> <li>■ sync-send: The interaction sends a request and does not expect to receive a response.</li> <li>■ sync-receive: The interaction expects to receive a response.</li> <li>■ async-send: Not applicable</li> </ul>
Input record	Identifies an input record.
Output record	Identifies an output record for the results of an interaction.
Interaction Specific Parameters	<p>Defines the properties and values of parameters specific to an interaction. The following property is available:</p> <p>transaction: The name of the IMS/TM transaction that is called when the interaction is executed.</p>

## Schema General Tab

Use the Schema General tab to define the general details of the input and output record structures for the interaction.

The Schema General tab is shown in the following figure:

Details

Name: Legacy

Version: 1.0

Header:

General | Interaction | Schema General | Schema Record | Source

The Schema General tab comprises fields, as listed in the following table:

Field	Description
Schema name	The name of the adapter.
Version	The schema version.
Header	A C header file to map between the data structure and the adapter.

## Schema Record Tab

Use the Schema Record tab to define the input and output record structures for the interaction.

The Schema Record tab is shown in the following figure.

Name	Type	Length
ORDERS	Record	
ORDER_KEY	string	
CUST_KEY	string	
ORDER_STATUS	string	
TOTAL_PRICE	string	
ORDER_DATE	string	
ORDER_PRIORITY	string	
CLERK	string	

Property	Value

General | Interaction | Schema General | **Schema Record** | Source

The Schema Record tab comprises fields, as listed in the following table:

Use the Fields List to define single data items within a record.

Field	Description
Name	Specifies the name of the field.
Type	<p>The data type of the field. The following are valid data types:</p> <ul style="list-style-type: none"> <li>Binary</li> <li>Boolean</li> <li>Date</li> <li>Double</li> <li>Float</li> <li>Int</li> <li>Long</li> <li>Numeric</li> <li>Short</li> <li>String</li> <li>Time</li> <li>Timestamp</li> <li>XML</li> </ul> <p><b>See Also:</b> <a href="#">Appendix B, "IMS/TM Back-end Adapter Data Type Support"</a> for details about the mapping from COBOL data types to IMS/TM back-end adapter data types.</p>

Field	Description
Length	The size of the field including a null terminator, when the data type supports null termination.

---

**Note:** Use the Specifications box to specify field properties.

---

**See Also:** [Appendix B, "IMS/TM Back-end Adapter Data Type Support"](#) for details about the mapping from COBOL data types to Oracle Connect data types.

## Source Tab

The Source tab displays the XML representation of the adapter metadata.

A sample Source tab is displayed in the following figure:

```
<?xml version="1.0" encoding="UTF-8"?>
<table name="customer" datasource="NAVDEMO" description=""
  fileName="D:\Program Files\Oracle\Server\demo\customer"
  nBlocks="0" nRows="0" bookmarkSize="4" organization="index">
  <fields>
    <field name="c_custkey" datatype="int4"/>
    <field name="c_name" datatype="cstring" size="25"/>
    <field name="c_address" datatype="cstring" size="40"/>
    <field name="c_nationkey" datatype="int4"/>
    <field name="c_phone" datatype="string" size="15"/>
    <field name="c_acctbal" datatype="double"/>
    <field name="c_mktsegment" datatype="string" size="10"/>
    <field name="c_comment" datatype="cstring" size="117" nullable="true"/>
  </fields>
  <keys>
    <key name="cindex" size="4">
      <segments>
        <segment name="c_custkey"/>
      </segments>
    </key>
  </keys>
</table>
```

# IMS/TM Back-end Adapter Data Type Support

OracleAS Adapter for IMS/TM supports a number of data types that are used to define metadata in Oracle Studio. The data types are mapped from the COBOL data types during the import procedure.

---

**Note:** The mapping of data types between OracleAS Adapter for IMS/TM and Oracle Application Server is performed internally by Oracle Connect.

---

This appendix contains the following section:

- [Data Type Mapping](#)

## Data Type Mapping

The COBOL data type COMP, in the table is an abbreviation for, and synonymous with, COMPUTATIONAL. Square brackets ( [ ] ) denote optional qualifiers for some COBOL compilers, which may not be allowed for other COBOL compilers.

**Table B-1 Data Type Mapping: COBOL and Oracle Connect Back-end Adapter**

COBOL Data Type	Oracle Connect Data Type
BINARY (with fractional data)	string
BINARY (without fractional data)	int
COMP (with fractional data)	string
COMP (without fractional data)	int
COMP-2	double
COMP-3	string
COMP-4 (with fractional data)	string
COMP-4 (without fractional data)	int
COMP-5 (with fractional data)	string
COMP-5 (without fractional data)	int
COMP-X (with fractional data)	string
COMP-X (without fractional data)	int
INDEX	int
[SIGN [IS]] LEADING	string

**Table B–1 (Cont.) Data Type Mapping: COBOL and Oracle Connect Back-end Adapter**

<b>COBOL Data Type</b>	<b>Oracle Connect Data Type</b>
[SIGN [IS]] LEADING SEPARATE [CHARACTER]	string
NATIVE-2	int
NATIVE-4	int
NATIVE-8	string
PACKED-DECIMAL	string
POINTER	int
[SIGN [IS]] TRAILING	string
[SIGN [IS]] TRAILING SEPARATE [CHARACTER]	string



---

## Advanced Tuning of the Daemon

The daemon configuration is managed using Oracle Studio. Daemon configuration is divided into the following groups:

- [Daemon Control](#)
- [Daemon Logging](#)
- [Daemon Security](#)
- [Workspaces](#)

### Daemon Control

Use the Daemon Control tab to define various daemon control options. The Daemon Control tab is accessed as follows:

1. From the **Start** menu, select **Programs, Oracle**, and then select **Studio**.
2. Select the computer defined in "[Setting Up the IBM OS/390 or z/OS Platform in Oracle Studio](#)" on page 2-14.
3. Right-click the computer and select **Open Runtime Perspective**.
4. Right-click the daemon in the Runtime Explorer and select **Edit Daemon Configuration**. The Daemon Control tab is displayed.
5. After making changes to the daemon, right-click the daemon and select **Reload Configuration**.


---

**Note:** You can also change daemon settings using the Configuration Explorer, by selecting a computer and scrolling the list to the required daemon. Right-click the daemon and select **Edit Daemon**.

Changes made to the daemon configuration are only implemented after the configuration is reloaded using the **Reload Configuration** option in the Runtime Manager perspective.

---

The Daemon Control tab is shown in the following figure:



The Daemon Control tab comprises fields, as described in the following table:

Field	Description
Automatically recover from failure	The daemon restarts automatically if it fails for any reason (any error that causes the daemon process to terminate, such as network process lost or the CPU running the daemon crashes and the backup daemon is defined on another CPU). All available and unconnected servers are terminated and any connected servers are marked and terminated on release. Also the backup starts a backup for itself. The backup appends a new log file to the log of the original daemon, adding a line indicating that a backup daemon was started.
Maximum XML request size	The maximum number of bytes that the daemon handles for an XML document.
Maximum XML in memory	The maximum amount of space reserved for the XML in memory.
Default language	The language that the daemon supports. This setting is used when working with a client with a code page different from the server code page.

Field	Description
Call timeout	<p>The timeout period for <i>short</i> calls for all daemons. The definition of a short call is a call that should be completed in a few seconds. For example, most calls to a database such as DESCRIBE should be completed in a few seconds as opposed to call like a GETROWS call, which can take a long time. In heavily loaded or otherwise slow systems, even short calls such as calls to open a file, may take a significant amount of time. If a short call takes more than the specified time to complete, the connection is stopped. The default value for this parameter is 60 seconds. Values of less than 60 seconds are considered to be 60 seconds.</p> <p>Specifying the timeout in a workspace overrides the value set in this field for that workspace.</p>
Connect timeout	<p>The time the client waits for a daemon server to start. If the daemon server does not start within this period, the client is notified that the server did not respond. The value specified for this parameter serves as the default timeout for all the workspaces listed in the daemon configuration. The default value for this parameter is 60 seconds.</p> <p>Specifying the timeout in a workspace overrides the value set in this field for that workspace.</p>
Client idle timeout	<p>The maximum amount of time any daemon client may be idle before the connection with the server is closed.</p> <p>Specifying the timeout in a Workspace overrides this setting for that workspace.</p>

## Daemon Logging

Use the Daemon Logging tab to define the daemon log file settings, the log file structure and the location where the log is saved. In addition, use it to define the data that is logged and traced in the file.

The Daemon Logging tab is accessed as follows:

1. From the **Start** menu, select **Programs, Oracle**, and then select **Studio**.
2. Select the computer defined in "[Setting Up the IBM OS/390 or z/OS Platform in Oracle Studio](#)" on page 2-14.
3. Right-click the computer and select **Open Runtime Perspective**.
4. Right-click the daemon in the Runtime Explorer and select **Edit Daemon Configuration**.
5. Click the Daemon Logging tab.
6. After making changes to the daemon, right-click the daemon and select **Reload Configuration**.

---


**Note:** You can also change daemon settings using the Configuration Explorer, by selecting a computer and scrolling the list to the required daemon. Right-click the daemon and select **Edit Daemon**.

Changes made to the daemon configuration are only implemented after the configuration is reloaded using the **Reload Configuration** option in the Runtime Manager perspective.

---

7. Right-click the daemon and select **End Unused Servers**. Any servers in the connection pool are closed and new servers start with the new configuration.

The Daemon Logging tab is shown in the following figure:



The Daemon Logging tab comprises fields, as listed in the following table:

Field	Description
Daemon log file location	Specifies the daemon produces its log data. The full path must be specified.
Logging options	Specifies what tracing is performed.
Client requests for server	Logs client requests for server activations; this provides logging of the process IDs of the started servers along with the location of the log files.
Administration requests for daemon	Logs all of the administration requests for the daemon.
Daemon operations	Logs all of the daemon operations.
Daemon logins	Logs daemon logins.
Daemon RPC function calls	Logs all daemon RPC function calls.
Daemon internal operations	Logs daemon internal operations.

Field	Description
Log trace information	Logs low-level RPC operations.
Display host and client domain name	Specifies whether the client host and domain name are logged rather than the client IP address. The default is false.
Trace options	Specifies the type of tracing being performed.
No timeout	Disables the standard RPC timeouts, setting them to a long duration (approximately an hour) to facilitate debugging.
Call trace	Generates a message in the server log file for each RPC function called. This is useful for troubleshooting the server.
RPC trace	Enables debugging messages on the server.
Sockets	Generates a message in the server log file for each socket operation.
Extended RPC trace	Generates a verbose message in the server log file for each low-level RPC function called. This is useful for troubleshooting the server.
System trace	Generates system-specific tracing of various operations.
Timing	Generates a timestamp for every entry to the server log file.
Server log filename format	Defines the name and location of the server log file. The field must specify the full path name. If no directory information is provided for the log file, it will be located in the login directory of the account running Oracle Connect workstation.

The following tokens can appear in the log file template and will be replaced accordingly:

- %A: workspace name
- %D: date (yymmdd)
- %I: instance number of the given workspace server
- %L: server account's login directory
- %P: server's process ID
- %T: time (hhmmss)
- %U: server's account name (username)

For example, %L/server\_%A%I.log may generate a log file such as: /usr/smith/server\_sales15.log. The default log file template is %L/server\_%A%I.log.

## Daemon Security

The Daemon Security tab is used to:

- Grant administration rights for the daemon.

- Determine access to the computer.

The Daemon Security tab is accessed as follows:

1. From the **Start** menu, select **Programs, Oracle**, and then select **Studio**.
2. Select the computer defined in "[Setting Up the IBM OS/390 or z/OS Platform in Oracle Studio](#)" on page 2-14.
3. Right-click the computer and select **Open Runtime Perspective**.
4. Right-click the daemon in the Runtime Explorer and select **Edit Daemon Configuration**.
5. Click the **Daemon Security** tab.
6. After making changes to the daemon, right-click the daemon and select **Reload Configuration**.

---


**Note:** You can also change daemon settings using the Configuration Explorer, by selecting a computer and scrolling the list to the required daemon. Right-click the daemon and select **Edit Daemon**.

Changes made to the daemon configuration are not implemented. They are only implemented after the configuration is reloaded using the **Reload Configuration** option in the Runtime Manager.

---

7. Right-click the daemon and select **End Unused Servers**. Any servers in the connection pool are closed and new servers start with the new configuration.

The Daemon Security tab is shown in the following figure:



The Daemon Security tab comprises fields, as listed in the following table:

Field	Description
Administrators privileges	Identifies the users (accounts) allowed to perform administrative tasks (tasks that require administrative login).
All users	Enables all users to access the daemon and change the settings.
Selected users only	The names of users (accounts) and groups that can be administrators. <sup>a</sup>  If a user is not specified, the account from which the daemon was started is considered the administrator. Note that the daemon does not require the user to log in to the account on the system, but to log in to the daemon using the account name and password.
Machine access	Manages access to the computer.
Allow anonymous login	Whether workspaces allow anonymous logins (without user name/password entries). For the optimal level of security, keep this option unchecked and define a username for the Daemon Administrators parameter. If unchecked, no workspace can have an anonymous client. If checked, a particular workspace allows anonymous clients.
Cached password	Enables login passwords to be cached. This enhances performance by reducing login times for future connections from the same client in a session.
Encryption methods	The encryption method being used to send information across the network. The default is an asterisk (*), meaning that all methods are acceptable. If an encryption method is specified, it must be used. The RC4 and DES3 protocols are currently supported.

<sup>a</sup> The name is prefixed with '@', to utilize the operating system GROUP feature.

## Workspaces

A daemon can include a number of workspaces. A workspace defines the server processes and environment that are used for the communication between the client and the server computer for the duration of the client request. Each workspace has its own definition. The workspace definition is divided into the following groups:

- [WS Info.](#)
- [WS Server](#)
- [WS Logging](#)
- [WS Security](#)
- WS Governing: This tab is not applicable for use with OracleAS Adapter for IMS/TM

## WS Info.

Use the WS Info. tab to specify the features that control the operation of the workspace, such as the server type, the command procedure used to start the workspace and the binding configuration associated with this workspace.

The WS Info. tab is accessed as follows:

1. From the **Start** menu, select **Programs, Oracle**, and then select **Studio**.
2. Select the computer defined in "[Setting Up the IBM OS/390 or z/OS Platform in Oracle Studio](#)" on page 2-14.
3. Right-click the computer and select **Open Runtime Perspective**.
4. Expand the daemon to display the workspaces in the Runtime Explorer.
5. Right-click the workspace and select **Edit Workspace Configuration**. The WS Info. tab is displayed.
6. After making changes to the workspace, right-click the daemon and select **Reload Configuration**.

---

**Note:** You can also change daemon settings using the Configuration Explorer, by selecting a computer and scrolling the list to the required daemon. Right-click the daemon and select **Edit Daemon**.

Changes made to the daemon configuration are not implemented. They are only implemented after the configuration is reloaded using the **Reload Configuration** option in the Runtime Manager.

---

7. Right-click the daemon and select **End Unused Servers**. Any servers in the connection pool are closed and new servers start with the new configuration.



The WS Info. tab is shown in the following figure:

The screenshot shows the 'IRPCD - Navigator' configuration window. The 'WS Info.' tab is selected. The fields are as follows:

- Workspace name: Navigator
- Description: A Navigator Server
- Startup script: /users/nav/navroot/bin/nav\_server
- Server type: native
- Workspace binding name: (empty)
- Workspace database name: (empty)
- Timeout parameters:
  - Client idle timeout: 0
  - Connect timeout: 60

The bottom tab bar includes: Daemon Control, Daemon Logging, Daemon Security, **WS Info.**, WS Server, WS Logging, WS Security, WS Governing, and Source.

The WS Info. tab comprises fields, as listed in the following table:

Field	Description
Workspace name	<p>The name used to identify the workspace.</p> <p><b>Note:</b> The default configuration includes the default Navigator Workspace. This workspace is automatically used if a workspace is not specified as part of the connection settings.</p>
Description	A description of the workspace.
Startup script	<p>The full path name of the script that starts the workspace server processes. The script specified here must always activate the <code>nav_login</code> procedure and then run the server program (<code>svc</code>). If you do not specify the directory, the startup procedure is taken from the directory where the daemon resides. Oracle Connect includes a default startup script, which it is recommended to use.</p>
Server type	This field is not applicable for use with OracleAS Adapter for IMS/TM.
Workspace binding name	This field is not applicable for use with OracleAS Adapter for IMS/TM.

Field	Description
Timeout parameters	<p>The time the client waits for the workspace server to start. If the workspace server does not start within this period, the client is notified that the server did not respond. Specifying the timeout here overrides the default setting, specified in the Control section.</p> <p><b>See Also:</b> "<a href="#">Daemon Control</a>" on page C-1 for details about the Daemon Control section.</p>
Client idle timeout	<p>The maximum amount of time a workspace client can be idle before the connection with the server is closed.</p>
Connect timeout	<p>The time the client waits for a workspace server to start. If the workspace server does not start within this period, the client is notified that the server did not respond. The value specified for this parameter serves as the default timeout for all the workspaces listed in the daemon configuration. The default value for this parameter is 60 seconds.</p>

## WS Server

Use the WS Server tab to specify the features that control the operation of the servers started up by the workspace and allocated to clients. For example, you can configure the workspace to start up a number of servers for future use, prior to any client request, instead of starting each server when a request is received from a client.

The WS Server tab is accessed as follows:

1. From the **Start** menu, select **Programs, Oracle** and then select **Studio**.
2. Select the computer defined in "[Setting Up the IBM OS/390 or z/OS Platform in Oracle Studio](#)" on page 2-14.
3. Right-click the computer and select **Open Runtime Perspective**.
4. Expand the daemon to display the workspaces in the Runtime Explorer.
5. Right-click the workspace and select **Edit Workspace Configuration**.
6. Select the WS Server tab.
7. After making changes to the workspace, right-click the daemon and select **Reload Configuration**.

---

**Note:** You can also change daemon settings using the Configuration Explorer, by selecting a computer and scrolling the list to the required daemon. Right-click the daemon and select **Edit Daemon**.

Changes made to the daemon configuration are not implemented. They are only implemented after the configuration is reloaded using the **Reload Configuration** option in the Runtime Manager.

---

8. Right-click the daemon and select **End Unused Servers**. Any servers in the connection pool are closed and new servers start with the new configuration.

The WS Server tab is shown in the following figure:

The screenshot shows the 'WS Server' tab in the 'IRPCD - Navigator' window. The window title is 'IRPCD - Navigator X'. The 'Workspace server mode' is set to 'multiClient'. The 'Reuse limit' section has 'None' selected. The 'Clients per server limit' section has 'None' selected. The 'Server availability' section has 'Initial number of servers' set to 0 and 'Minimum number of available servers' set to 0. The 'Resource limitations' section has 'Limit number of active servers' set to 0. The 'Server priority' section has 'Use default priority' selected. The bottom of the window shows a tab bar with the following tabs: Daemon Control, Daemon Logging, Daemon Security, WS Info., WS Server (selected), WS Logging, WS Security, WS Governing, and Source.

IRPCD - Navigator X

Workspace server mode: multiClient

Reuse limit:  
☒ None  
☐ Maximum: 0

Clients per server limit:  
☒ None  
☐ Maximum: 0

Server availability:  
Initial number of servers: 0 Minimum number of available servers: 0  
☐ Keep when daemon ends ☐ Set maximum number of servers: 0

Resource limitations:  
☐ Limit number of active servers: 0

Server priority:  
☒ Use default priority  
☐ Use priority specified: 0

Daemon Control | Daemon Logging | Daemon Security | WS Info. | **WS Server** | WS Logging | WS Security | WS Governing | Source

The WS Server tab comprises fields, as listed in the following table:

Field	Description
Workspace server mode	<p>Specifies the type of new server processes that the daemon starts up. The daemon supports the following server modes:</p> <ul style="list-style-type: none"> <li>■ <b>singleClient:</b> Each client receives a dedicated server process. The account in which a server process runs is determined either by the client login information or by the specific server workspace.  This mode enables servers to run under a particular user account and isolates clients from each other (because each receives its own process). However, this server mode incurs a high overhead due to process startup times and can use a lot of server resources (because it requires as many server processes as concurrent clients).</li> <li>■ <b>multiClient:</b> Clients share a server process and are processed serially. This mode has low overhead because the server processes are already initialized. However, because clients share the same process, they can impact one another, especially if they issue lengthy queries. The number of clients that share a process is determined by the Clients per server limit field.</li> <li>■ <b>multiThreaded:</b> This field is not applicable for use with OracleAS Adapter for IMS/TM.</li> <li>■ <b>reusable:</b> An extension of single-client mode. Once the client processing finishes, the server process does not die and can be used by another client, reducing startup times and application startup overhead.  This mode does not have the high overhead of single-client mode because the servers are already initialized. However, this server mode can use a lot of server resources (because it requires as many server processes as concurrent clients).</li> </ul> <p><b>Note:</b> The other modes can be set so that the server processes are reusable. The number of times a process can be reused is controlled by the Reuse limit field value.</p>
Reuse limit	<p>Specifies the maximum number of times a particular server can be reused. A one-client server can be reused after its (single) client has disconnected. Reuse of servers enhances startup performance because it avoids the need to repeat initialization. The default for this field is none (0), indicating that server reuse is unlimited. This parameter is disabled only if the server mode value is singleClient.</p>

Field	Description
Clients per server limit	The maximum number of clients a server process for the current workspace accepts. The default for this field is none (0), indicating that the number of clients for each server is unlimited. This field is enabled only if the server mode value is multiClient or multiThreaded.
Server availability	<p>Specifies the number of servers in a pool of servers, available to be assigned to a client.</p> <ul style="list-style-type: none"> <li>Initial number of servers: The number of server processes that are prestarted for this workspace when the daemon starts up. When the number of available server processes drops lower than the value specified in the Minimum number field, the daemon again starts server processes until this number of available server processes is reached. The default for this field is zero.</li> <li>Minimum number: The minimum number of server processes in the prestarted pool before the daemon resumes creating new server processes (to the value specified in the Initial number of servers field). If this field is set to a value higher than the Initial number of servers field, the daemon uses the value specified in the Initial number of servers field. The default for this field is 0.</li> <li>Keep when daemon ends: When a daemon is shutdown, all the servers started by that daemon are also killed, even if they are active. Set this field to true if you want the servers for the workspace to remain active, even after the daemon has been shut down. If this field is set to true, it is the responsibility of the system operator or manager to ensure that the servers are eventually killed. This must be done at the system level.</li> <li>Set maximum number of servers: The maximum number of available server processes. Once this number is reached, no new nonactive server processes are created for the particular workspace. For example, if a number of server processes are released at the same time, so that there are more available server processes than specified by this field, the additional server processes higher than this value are terminated. The default for this field is zero, meaning that there is no maximum.</li> </ul>

Field	Description
resource limitations	<p>Specifies the number of servers that can be in use at any one time. The more servers used, the greater the system resources that are used.</p> <ul style="list-style-type: none"><li>■ Number of subtasks: The number of subtasks for a server that are prestarted for this workspace when the daemon starts up. Thus, setting 10 prestarted servers and 10 subtasks results in 100 tasks started (10 subtasks for each process).</li><li>■ Limit number of active servers: The maximum number of active server processes (either available or in use). Once reached, no new server processes will be created for the particular workspace and client connections would be rejected if there is no available server to accept them. Once the number of active servers drops lower than the maximum (for example, a client disconnects from a server and the server terminates), new servers can again be started. If the value of this field is set to a nonzero value lower than the value for the Initial number of servers field, the daemon assumes it is set to the same value as the Initial number of servers field. The default for this field is zero, meaning that no maximum is enforced.</li></ul>
Server Priority	<p>The priority for servers. For example, a workspace for applications with online transaction processing can be assigned a higher priority than a workspace that requires only query processing.</p> <ul style="list-style-type: none"><li>■ Use default priority: Sets the priority as 0. There is no specific priority for this workspace.</li><li>■ Use priority: Enables setting the priority.</li></ul>

## WS Logging

Use the WS Logging tab to specify parameters to log, that occur with the workspace server process.

The WS Logging tab is accessed as follows:

1. From the **Start** menu, select **Programs, Oracle** and then select **Studio**.
2. Select the computer defined in "[Setting Up the IBM OS/390 or z/OS Platform in Oracle Studio](#)" on page 2-14.
3. Right-click the computer and select **Open Runtime Perspective**.
4. Expand the **Daemons** node to display the workspaces in the Runtime Explorer.
5. Right-click the workspace and select **Edit Workspace Configuration**.
6. Select the WS Logging tab.
7. After making changes to the workspace, right-click the daemon and select **Reload Configuration**.

---


**Note:** You can also change daemon settings using the Configuration Explorer, by selecting a computer and scrolling the list to the required daemon. Right-click the daemon and select **Edit Daemon**.

Changes made to the daemon configuration are not implemented. They are only implemented after the configuration is reloaded using the **Reload Configuration** option in the Runtime Manager.

---

8. Right-click the daemon and select **End Unused Servers**. Any servers in the connection pool are closed and new servers start with the new configuration.

The WS Logging tab is shown in the following figure:



The WS Logging tab comprises fields, as listed in the following table:

Field	Description
Specific log file format	<p>Defines the name and location of the server log file if you want the data written to a file instead of SYSOUT for the server process. The parameter must specify the name and the high level qualifier.</p> <p>The following tokens can appear in the log file template and will be replaced accordingly:</p> <ul style="list-style-type: none"> <li>■ %A: workspace name.</li> <li>■ %D: date (yymmdd).</li> <li>■ %I: instance number of the given workspace server.</li> <li>■ %L: server account's login directory.</li> <li>■ %P: server's process ID.</li> <li>■ %T: time (hhmmss).</li> <li>■ %U: server's account name (username).</li> </ul>

Field	Description
Trace options	<p>Specifies the type of tracing to be performed. The following options are available:</p> <ul style="list-style-type: none"><li>■ No timeout: Disables the standard RPC timeouts, setting them to a long duration (approximately an hour) to facilitate debugging.</li><li>■ Call trace: Generates a message in the server log file for each RPC function called. This is useful for troubleshooting the server.</li><li>■ RPC trace: Enables debugging messages on the server.</li><li>■ Sockets: Generates a message in the server log file for each socket operation. This is useful for troubleshooting client/server communication - providing a detailed trace of every client/server communication.</li><li>■ Extended RPC trace: Generates a verbose message in the server log file for each low-level RPC function called. This is useful for troubleshooting the server.</li><li>■ System trace: Generates operating system-specific tracing.</li><li>■ Timing: Generates a timestamp for every entry to the server log file.</li></ul>
Logging	<p>Specifies the level of events that are logged for the workspace. The following levels are available:</p> <ul style="list-style-type: none"><li>■ none: The event log only displays the IP addresses of client that have logged in and out from the workspace.</li><li>■ error: The event log displays the IP addresses of client that have logged in and out from the workspace as well as any errors that have been generated.</li><li>■ debug: The event log displays the IP addresses of client that have logged in and out from the workspace as well as any errors that have been generated and all trace results that were specified in the Daemon Logging tab.</li></ul>
Server	<p>Specifies the server connection events.</p> <ul style="list-style-type: none"><li>■ Connect: The event log displays server connection events.</li><li>■ Disconnect: The event log displays server disconnect events.</li></ul>
Client	<p>Specifies what tracing is performed.</p> <ul style="list-style-type: none"><li>■ Connect: The event log displays client connection events.</li><li>■ Disconnect: The event log displays client disconnect events.</li></ul>
Audit	<p>This group is not applicable for use with OracleAS Adapter for IMS/TM.</p>

## WS Security

Use the WS Security tab to specify the level of security at the workspace level, as opposed to the daemon level, which is set in the Security tab of the daemon.



**See Also:** ["Daemon Security"](#) on page C-5 for details about security.

The WS Security tab is used to:

- Grant administration rights for the workspace
- Determine access to the workspace by a client

The WS Security tab is accessed as follows:

1. From the **Start** menu, select **Programs, Oracle** and then select **Studio**.
2. Select the computer defined in ["Setting Up the IBM OS/390 or z/OS Platform in Oracle Studio"](#) on page 2-14.
3. Right-click the computer and select **Open Runtime Perspective**.
4. Expand the **Daemon** to display the workspaces in the Runtime Explorer.
5. Right-click the workspace and select **Edit Workspace Configuration**.
6. Select the WS Security tab.
7. After making changes to the workspace, right-click the daemon and select **Reload Configuration**.

---

---

**Note:** You can also change daemon settings using the Configuration Explorer, by selecting a computer and scrolling the list to the required daemon. Right-click the daemon and select **Edit Daemon**.

Changes made to the daemon configuration are not implemented. They are only implemented after the configuration is reloaded using the **Reload Configuration** option in the Runtime Manager.

---

---

8. Right-click the daemon and select **End Unused Servers**. Any servers in the connection pool are closed and new servers start with the new configuration.

The WS Security tab is shown in the following figure:

The WS Security tab comprises fields, as listed in the following table:

Field	Description
Administration	Defines the users (accounts) allowed to perform administrative tasks (tasks that require administrative login) on this workspace.
Administrator privileges	<p>Identifies the users (accounts) with administrator privileges).</p> <ul style="list-style-type: none"> <li>All users: Indicates that anyone can access the workspace and change the settings.</li> <li>Selected users only: The names of users (accounts) and groups that can be administrators.</li> </ul> <p><b>Note:</b> If a user is not specified here, the user specified in the Workspace users field will have administrator rights for this workspace. In this case, if all users are selected for the Workspace users field, then all users have administrator rights for this workspace.</p> <ul style="list-style-type: none"> <li>Allow Listing: Determines whether this workspace appears in the list of workspaces</li> </ul>
Workspace access	Defines the users (accounts) allowed to access the workspace, firewall access ports, workspace account, and anonymous login permissions.

Field	Description
Workspace users	<p>Lists the users who are allowed to use the workspace.</p> <ul style="list-style-type: none"><li>■ All users: Indicates that any user who has logged on to the daemon can use the workspace.</li><li>■ Selected users only: Specifies users (accounts) and groups that can use the workspace.</li></ul> <p><b>Note:</b> If a user is not specified, any user who has logged on to the daemon can use the workspace.</p> <ul style="list-style-type: none"><li>■ Enable ports range: Defines the firewall ports through which you access the workspace. Specifies the range of ports available for this workspace when starting server processes. Use this option when you want to control the port number, so that Oracle Connect can be accessed through a firewall.</li><li>■ Use specific workspace account: Defines the operating system account used for the workspace. If not specified, the account name that was provided by the client is used.</li><li>■ Allow anonymous client login to server account: Defines whether this workspace can be invoked without authentication (user name/password). If anonymous login is allowed, specify the server account name to use. If this field is not specified, the value in the Workspace account field is used.</li></ul>



---

## Globalization Settings

OracleAS Adapter for IMS/TM provides the globalization support for the following languages:

- Arabic
- English (the default)
- Hebrew
- Japanese
- Korean
- Simple Chinese
- Spanish
- Traditional Chinese


This appendix describes how to define the language support.

### Defining the Language and Codepage

Perform the following steps to define the required language and codepage.

1. From the **Start** menu, select **Programs, Oracle**, and then select **Studio**.
2. Select the computer defined in "[Setting Up the IBM OS/390 or z/OS Platform in Oracle Studio](#)" on page 2-14.
3. Right-click **NAV** and select **Edit Binding**.
4. In the Binding Properties tab, expand the **misc** node.

The NAV binding Properties tab is shown in the following figure:



5. Enter a valid value for the language. The following language codes are valid:

- ARA: Arabic
- ENG: English
- HEB: Hebrew
- JPN: Japanese
- KOR: Korean
- SCHI: Simple Chinese
- SPA: Spanish
- TCHI: Traditional Chinese

6. Optionally, in the **codepage** field, specify the codepage required.

You can skip this step, and specify a language (see the previous step). In this case, a default codepage is used. The following shows the default codepages:

- ARA: AR8ISO8859P6
- ENG: EBCDIC
- HEB: IW8EBCDIC424
- JPN: JA16JDBC
- KOR: KO16JDBC
- SCHI: ZHS16JDBC
- SPA: WE8EBCDICLATIN
- TCHI: ZHT16JDBC

---

---

# Index

## A

---

acxTrace parameter, 6-6  
analyzerQueryPlan parameter, 6-6  
application language  
    parameter, 6-7

## B

---

buffer size  
    comCacheBufferSize parameter, 6-5

## C

---

CD-ROM drive requirements  
    IBM S/390, 2-2  
    PC, 2-2  
codepage parameter, 6-6  
comCacheBufferSize, 6-5  
comCacheBufferSize parameter, 6-5  
comm parameters  
    comCacheBufferSize, 6-5  
    comMaxSocketSize, 6-5  
    comMaxXmlSize, 6-5, 6-6  
comMaxSocketSize parameter, 6-5  
comMaxXmlSize parameter, 6-5, 6-6  
cvtSeverityLevel parameter, 6-7

## D

---

daemon  
    logging, C-3  
    security, C-5  
    server modes, 6-2  
    shutting down, 5-2  
    starting, 5-1  
    timeout, 5-6  
daemon configuration  
    logging section, C-3  
    security section, C-5  
data type conversions  
    cvtSeverityLevel parameter, 6-7  
data types  
    cvtSeverityLevel, 6-7  
    nlsString, 6-7  
datatypes  
    metadata atomic datatypes, B-1

debug environment parameters, 6-6  
debug parameters  
    acxTrace, 6-6  
    analyzerqueryPlan, 6-6  
    generalTrace, 6-6  
    logFile, 6-6  
    oledbTrace, 6-6  
    optimizerTrace, 6-6  
    queryWarnings, 6-6  
    traceDir, 6-6  
disk space requirements  
    IBM S/390, 2-2  
    PC, 2-2

## E

---

edit parameter, 6-7  
environment parameters  
    acxTrace, 6-6  
    analyzerQueryPlan, 6-6  
    codepage, 6-6  
    comCacheBufferSize parameter, 6-5  
    comMaxSocketSize, 6-5  
    comMaxXmlSize, 6-5, 6-6  
    cvtSeverityLevel, 6-7  
    debug, 6-6  
    edit, 6-7  
    generalTrace, 6-6  
    language, 6-7  
    logFile, 6-6  
    miscellaneous, 6-6  
    nlsString, 6-7  
    odbc, 6-8  
    oledb, 6-8  
    oledbTrace, 6-6  
    optimizer, 6-8  
    optimizerTrace, 6-6  
    queryProcessor, 6-8  
    queryWarnings, 6-6  
    tempDir, 6-7  
    traceDir, 6-6  
    transactions, 6-9  
    tuning, 6-9  
    year2000Policy, 6-8  
error log  
    logFile parameter, 6-6

## G

---

generalTrace parameter, 6-6  
Generating Inbound Interactions, 2-26

## H

---

hardware requirements  
IBM S/390 CD-ROM drive, 2-2  
IBM S/390 disk space, 2-2  
IBM S/390 memory, 2-2  
PC CD-ROM drive, 2-2  
PC disk space, 2-2  
PC memory, 2-2  
PC processor, 2-2  
UNIX, 2-2

## I

---

IBM S/390  
installation, 2-5  
postinstallation, 2-8  
preinstallation, 2-4  
installation  
IBM S/390, 2-5  
installing  
Windows, 2-14

## L

---

language parameter, 6-7  
log files  
daemon options, C-3  
logFile parameter, 6-6  
logFile parameter, 6-6  
logging  
optimizer strategy, 6-6  
trace information, 6-6

## M

---

maximum size, 6-5  
memory requirements  
IBM S/390, 2-2  
PC, 2-2  
metadata  
atomic datatypes, B-1  
Microsoft software requirements, 2-2  
miscellaneous environment parameters, 6-6  
miscellaneous parameters  
codepage, 6-6  
cvtSeverityLevel, 6-7  
edit, 6-7  
language, 6-7  
nlsString, 6-7  
tempDir, 6-7  
year2000Policy, 6-8  
Modeling Interactions, 2-18

## N

---

NAV\_UTIL  
text editor, 6-7  
nlsString parameter, 6-7

## O

---

odbc environment parameters, 6-8  
oledb environment parameters, 6-8  
oledbTrace parameter, 6-6  
operating system requirements  
PC, 2-2  
UNIX, 2-2  
optimizer environment parameters, 6-8  
optimizer files  
traceDir parameter, 6-6  
optimizer plan  
writing to file, 6-6  
optimizerTrace parameter, 6-6  
Oracle Application Server requirements, 2-2

## P

---

postinstallation  
IBM S/390, 2-8  
preinstallation  
IBM S/390, 2-4  
processor requirements  
PC, 2-2  
UNIX, 2-2

## Q

---

query optimizer  
logging strategy, 6-6  
writing plan to file, 6-6  
query optimizer files  
traceDir parameter, 6-6  
queryProcessor environment parameters, 6-8  
queryWarnings parameter, 6-6

## R

---

requirements  
PC hardware requirements, 2-2  
PC software requirements, 2-2  
UNIX hardware requirements, 2-1  
UNIX software requirements, 2-2

## S

---

server modes  
configuring, 6-2  
servers  
reusable, 6-3  
Reuse limit daemon parameter, C-12  
ReuseLimit daemon parameter, 6-3  
Setting up Runtime User Access, 2-17  
SMS  
system managed storage, 2-4



- sockets
  - comMaxSocketSize parameter, 6-5
- software
  - Microsoft products, 2-2
- software requirements
  - Microsoft, 2-2
  - Oracle Application Server, 2-2
  - PC operating system, 2-2
  - UNIX operating system, 2-2
- system managed storage
  - SMS, 2-4

## **T**

---

- tempDir parameter, 6-7
- temporary files
  - tempDir parameter, 6-7
- timeout
  - client idle, 5-6
- trace information
  - logging, 6-6
- traceDir parameter, 6-6
- transactions environment parameters, 6-9
- tuning environment parameters, 6-9

## **W**

---

- Windows
  - installing, 2-14
- Workspace server mode, C-12

## **X**

---

- XML documents, 6-5
  - maximum size, 6-6

## **Y**

---

- Y2K
  - year2000Policy parameter, 6-8

